

Eaton 16NHM000B-690

Catalog Number: 16NHM000B-690

Eaton Bussmann series low voltage NH Fuse, 690V, 16A, 120 kAIC, Combination fuse status indicator, fuse, Class aM

General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage NH Fuse	16NHM000B-690
	UPC
	051712240659
EAN	Product Length/Depth
5027590437813	79 mm
Product Height	Product Width
51 mm	21 mm
Product Weight	Warranty
132 g	Not Applicable
Compliances	Certifications
RoHS Compliant	IEC 60269-1
CE Marked	IEC 60269-2
	DIN 43620



Product specifications

Interrupt rating

120 kAIC

Insulated metal gripping lugs (IMGL)

No

Current type

AC

Suitable for

Microswitch 170H0236

EBF Vertical fuse rail

EBV Vertical fuse switch-disconnectors

EBH Size 000 Horizontal fuse switch-disconnectors

Amperage Rating

16 A

Frequency rating - max

62 Hz

Fuse type

Square body with knife blade contact

Fitted with:

Metal gripping lugs

Rated switching capacity

120 kA

Fuse size

NH000

Rated switching capacity AC

120 kA

Voltage rating

690 V

Fuse indicator

Combination fuse status indicator

Construction

NH000

Construction size

NH000

Rated voltage AC

690 V

Connection

Resources

Catalogs

NH Fuse links, bases and gear

Bussmann series complete full line catalog no. 1007

Compliance information

CE 690V NH Motor rated

UKCA 690V NH Motor rated

Presentations

NH Overview Video

Technical data sheets

10165 NH 500 and 690 Volts aM

Blade end

Quantity

3

Material

Ceramic body

Utilization category

aM (switchgear protection)

Watt losses

0.8 W

Type

Fuse

Fuse shape

Knife blade contacts

Square body

Breaking capacity

120 kA

Frequency rating - min

45 Hz

Class

Class aM

Application

industrial

Voltage type

AC

Packaging type

Standard