

Eaton 20H07-660

Catalog Number: 20H07-660

Fuse-link, low voltage, 20 A, AC 690 V, DC 460 V, BS88/A2, 22 x 82 mm, gL/gG, BS

General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage	20H07-660
British standard fuse	UPC
	051712674379
EAN	Product Length/Depth
5027590467872	84.5 mm
Product Height	Product Width
21 mm	21 mm
Product Weight	Warranty
48.5 g	Not Applicable
Compliances	
Contact Manufacturer	



Electrical rating

Amperage Rating

20 A

Breaking capacity

80 kA

Interrupt rating

80 kAIC

Rated switching capacity

80 kA

Voltage rating

690 V

Voltage type

AC/DC

Physical details

Color

None

Fuse type

H07-660

General information

Class

Class gG/gL

Connection

Bolt-on

Construction size

A2

Fitted with:

Offset bolted tags

Fuse indicator

None

Fuse shape

Offset bolted tags

Fuse size

BS88/A2

Insulated metal gripping lugs (IMGL)

No

Utilization category

gG (cable protection/equipment protection)

Resources

Catalogs

[Bussmann series complete full line catalog no. 1007](#)

Compliance information

[UKCA BS88-2 660V Industrials, H07-660](#)

[CE BS88-2 660V Industrials, H07-660](#)

Technical data sheets

[4150 H07-660 fuses](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)