

Eaton 2NHG000B-400

Catalog Number: 2NHG000B-400

Fuse-link, LV, 2 A, AC 400 V, NH000, gL/gG, IEC, dual indicator, live gripping lugs

General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage NH Fuse	2NHG000B-400
	UPC
	051712241946
EAN	Product Length/Depth
5027590472807	79 mm
Product Height	Product Width
51 mm	21 mm
Product Weight	Warranty
131 g	Not Applicable
Compliances	Certifications
RoHS Compliant	IEC 60269-1
CE Marked	IEC 60269-2
	DIN 43620



Product specifications

Interrupt rating

120 kAIC

Insulated metal gripping lugs (IMGL)

No

Current type

AC

Suitable for

Microswitch 170H0236

EBF Vertical fuse rail

EBV Vertical fuse switch-disconnectors

EBH Size 000 Horizontal fuse switch-disconnectors

Amperage Rating

2 A

Frequency rating - max

62 Hz

Fuse type

Square body with knife blade contact

Fitted with:

Metal gripping lugs

Rated switching capacity

120 kA

Fuse size

NH000

Rated switching capacity AC

120 kA

Voltage rating

400 V

Fuse indicator

Combination fuse status indicator

Construction

NH000

Construction size

NH000

Rated voltage AC

400 V

Connection

Resources

Catalogs

NH Fuse links, bases and gear

Bussmann series complete full line catalog no. 1007

Compliance information

CE NH Size 000, 400V fuse-links

UKCA NH Size 000, 400V fuse-links

Presentations

NH Overview Video

Specifications and datasheets

Eaton Specification Sheet - 2NHG000B-400

Blade end

Quantity

3

Material

Ceramic body

Utilization category

gL/gG (cable protection/equipment protection)

Watt losses

0.8 W

Type

Fuse

Fuse shape

Square body

Knife blade contacts

Breaking capacity

120 kA

Frequency rating - min

45 Hz

Class

Class gG/gL

Application

industrial

Utilities, Solar, Wind

Voltage type

AC

Packaging type

Standard