

Eaton 2NHG000B-690

Catalog Number: 2NHG000B-690

Eaton Bussmann series low voltage NH Fuse, Live gripping lug, 690V, 2A, 120 kAIC, Combination fuse status indicator, fuse, Blade end connection, Class C gL/gG, Square-body with knife blade contact, Ceramic body

General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage NH Fuse	2NHG000B-690
	Model Code
	NH FUSE 2A 690V SIZE-000 GG MGL
UPC	EAN
051712193009	5027590472814
Product Length/Depth	Product Height
79 mm	51 mm
Product Width	Product Weight
21 mm	151.3333333 g
Warranty	Compliances
Not Applicable	RoHS Compliant
	CE Marked
Certifications	
IEC 60269-1	
IEC 60269-2	
DIN 43620	



Product specifications

Interrupt rating

120 kAIC

Insulated metal gripping lugs (IMGL)

No

Suitable for

Microswitch 170H0236

EBF Vertical fuse rail

EBV Vertical fuse switch-disconnectors

EBH Size 000 Horizontal fuse switch-disconnectors

Amperage Rating

2 A

Frequency rating - max

62 Hz

Fuse type

Square body with knife blade contact

Fitted with:

Metal gripping lugs

Rated switching capacity

120 kA

Fuse size

NH000

Rated switching capacity AC

120 kA

Voltage rating

690 V

Fuse indicator

Combination fuse status indicator

Special features

Live gripping lug

Construction

NH000

Construction size

NH000

Rated voltage AC

690 V

Connection

Resources

Catalogs

[NH Fuse links, bases and gear](#)

[Bussmann series complete full line catalog no. 1007](#)

Compliance information

[CE NH Size 000, 690V fuse-links](#)

[UKCA NH Size 000, 690V fuse-links](#)

Presentations

[NH Overview Video](#)

Specifications and datasheets

[Eaton Specification Sheet - 2NHG000B-690](#)

Blade end

Quantity

3

Material

Ceramic body

Utilization category

gL/gG (cable protection/equipment protection)

Watt losses

4 W

Type

Fuse

Fuse shape

Knife blade contacts

Square body

Breaking capacity

120 kA

Frequency rating - min

45 Hz

Class

Class gG/gL

Application

industrial

Utilities, Solar, Wind

Voltage type

AC

Packaging type

Standard