



Actual

Catalog Number: MDBOOT-SEAL
Product ID: 7TAH007720R0018
UPC Number: 78621071367
Status: A

KUBE Sealant for use with T&B Motor Disconnect Boots, Width 1 Inch, Length 10 Feet, Thickness 1/8 Inch, Polybutene Compound

- Resists acids, bases and alcohols.
- Passes VO Vertical Flame test.
- #N/A
- The cable should be clean and free of grease and other foreign substances. Apply two layers around each cable at the same distance from the connector. Slide the assembly into boot, apply Ty-Rap cable ties and work sealant around wires at end of boot to eliminate voids.

North American Specifications (UNSPSC)

UNSPSC	39121337 Electrical sealing compound
IGCC	4496 Electrical sealing compound
Brand Name	Color-Keyed
Type	Motor Disconnect Boot Sealant
Special Features	Resists acids, bases and alcohols.
Application	The cable should be clean and free of grease and other foreign substances. Apply two layers around each cable at the same distance from the connector. Slide the assembly into boot, apply Ty-Rap cable ties and work sealant around wires at end of boot to eliminate voids.
Size	10-Foot
Temperature Range	40 to 180 F
Material	Polybutene Compound

European Specifications (ETIM)

ETIM	EC002722 Jointing compound
Model	Other
Packaging	Other

Packaging

Inner Quantity	1
Inner Dimensions (inches)	10x8x.5
Outer Quantity	5
Outer Dimensions (inches)	8.5x7.2x6
Weight Uom	71 lbs. per 100

Documents / Support Tools

Technical Drawing / Data Sheet US	Available on Website
Instruction Sheet	TA00899-TB2
Safety Data Sheet (SDS) Global	SDS-00046-TB2

For further technical assistance, please contact us...

ABB Installation Products - USA
 860 Ridge Lake Blvd.
 Memphis, TN 38120
www.tnb.com

ABB Installation Products Technical Support
 MS 3B-50
 860 Ridge Lake Blvd.
 Memphis, TN 38120

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com