


Utility Boxes and Accessories

4" x 2 1/8" Utility Boxes




58351 1/2*




58351 B 1/4
B bracket recessed 1/4"




58361 1/2*




58361 3/4



58361 V 1/2*
CV bracket recessed 1/2"



58371 1/2*



58371 3/4



58371 T 1/2
T bracket recessed 5/8"




58371V1/2-25*
CV bracket recessed 1/2"


CAT. NO.	DEPTH (IN.)	CU. IN. CAPACITY	BRKTS.	KNOCKOUTS (IN.)			STD CTN.
				EA. SIDE CONDUIT	EA. END CONDUIT	BOTTOM CONDUIT	
<i>With Conduit KOs</i>							
58351 1/2*	1½	10.3	—	3–½	1–½	2–½	50
58351 B 1/4	1½	10.3	B	3–½	1–½	2–½	25
58361 1/2*	1⅝	13.0	—	3–½	1–½	2–½	50
58361 3/4	1⅝	13.0	—	2–¾	1–¾	2–¾	50
58361 V 1/2*	1⅝	13.0	CV	3–½	1–½	2–½	50
58371 1/2*	2⅝	14.5	—	3–½	1–½	2–½	50
58371 3/4	2⅝	14.5	—	2–¾	1–¾	2–¾	50
58371 T 1/2*	2⅝	14.5	T	3–½	1–½	2–½	25
58371V1/2-25*	2⅝	14.5	CV	3–½	1–½	2–½	25

* Factory-provided raised ground-screw location.

4 1/8" x 2 1/2" Utility Boxes



68361 1/2



68371 1/2


CAT. NO.	DEPTH (IN.)	CU. IN. CAPACITY	KNOCKOUTS (IN.)			STD. CTN.
			EA. SIDE CONDUIT	EA. END CONDUIT	BOTTOM CONDUIT	
<i>With Conduit KOs</i>						
68361 1/2*	1 ⁵ / ₈	17.0	3- ¹ / ₂	1- ¹ / ₂	2- ¹ / ₂	25
68371 1/2*	2 ³ / ₈	18.8	3- ¹ / ₂	1-1 ¹ / ₂	2- ¹ / ₂	50
* Factory-provided raised ground-screw location.						

* Factory-provided raised ground-screw location.

4" x 2 1/8" Utility Box Covers



58 C 1



58 C 4




58 C 5




58 C 6




58 C 7



58 C 11



58 C 16



58 C 30

CAT. NO.	DIA. HOLE (IN.)	DESCRIPTION	STD. CTN.
Raised 1/4"			
58 C 1	—	Blank	100
58 C 4	1 1/2	For 4-wire twist-lock single flush receptacle	25
58 C 5	1 1/2	For single receptacle	25
58 C 6	—	With 1/2" KO	25
58 C 7	—	For duplex flush receptacle	100
58 C 11	—	With 1 1/2" bushed hole	25
58 C 16	—	For single GFCI receptacle	25
58 C 30	—	For one toggle switch	100

Includes captivated Phillips head screws.