



Switch boxes and accessories


Gangable switch boxes - 2" deep




51



51-NE



51-LC




51-FB

Gangable switch boxes - 2" deep


Cat. No.	Capacity (cu. in.)	Description	Std. Ctn.
51	10.0	2" deep x 3" long x 2" wide Two 1/2" KOs in each of two sides, one 1/2" KO in each end and two 1/2" KOs in bottom. Two nail holes in sides. Furnished with plaster ears*	50
51-NE	10.0	2" deep x 3" long x 2" wide Two 1/2" KOs in each of two sides, one 1/2" KO in each end and two 1/2" KOs in bottom. Two nail holes in sides*	50
51-LC	10.0	For non-metallic cable, 2" deep x 3" long x 2" wide Two 1/2" KOs in each of two sides, two loom KOs in each end and one 1/2" KO in bottom. Furnished with plaster ears. One loom clamp for use on non-metallic sheathed cable with 10/32 deep-slotted screw assembled. Two nail holes in sides*	50
51-FB	10.0	2" deep x 3" long x 2" wide Two 1/2" KOs in one side, flat bracket on other side, one 1/2" KO in each end and two 1/2" KOs in bottom. Bracket offset 9/16" from face*	50

*Uses Steel City® 100 series covers.


Gangable switch boxes - 2 1/2" deep




52




52-3/4-BW



52-NE




52-NE-3/4



52-LCNE



52-FB-3/4



52-FBC

Gangable switch boxes - 2 1/2" deep

Cat. No.	Capacity (cu. in.)	Description	Std. Ctn.
52	12.5	2 1/2" deep x 3" long x 2" wide Two 1/2" KOs in each of two sides, one 1/2" KO in each end and two 1/2" KOs in bottom. Furnished with plaster ears. Four nail holes in sides*	50
52-3/4-BW	12.5	2 1/2" deep x 3" long x 2" wide Two 1/2" KOs in each of two sides, one 3/4" KO in each end and two 1/2" KOs in bottom. Furnished with plaster ears. Four nail holes in sides*	50
52-NE	12.5	2 1/2" deep x 3" long x 2" wide Two 1/2" KOs in each of two sides, one 1/2" KO in each end and two 1/2" KOs in bottom. Four nail holes in sides*	50
52-NE-3/4	12.5	2 1/2" deep x 3" long x 2" wide Two 1/2" KOs in each of two sides, one 3/4" KO in each end and two 1/2" KOs in bottom. Four nail holes in sides*	50
52-LCNE	12.5	For non-metallic cable, 2 1/2" deep x 3" long x 2" wide Two 1/2" KOs in each side, two loom KOs and one 1/2" KO in each end. One 1/2" KO in bottom. One loom clamp for use on non-metallic sheathed cable with 10/32 deep-slotted screw assembled. Four nail holes in sides*	50
52-FB-3/4	12.5	2 1/2" deep x 3" long x 2" wide Two 1/2" KOs in one side, flat bracket on other side, one KO in each end and two 3/4" KOs in bottom. Flat bracket offset 9/16" from face*	50
52-FBC	12.5	For non-metallic cable, 2 1/2" deep x 3" long x 2" wide Two 1/2" KOs in one side, flat bracket on other side, two loom KOs and one 1/2" KO in each end and one 1/2" KO in bottom. One loom clamp for use on non-metallic sheathed cable with 10/32 deep-slotted screw assembled. Flat bracket offset 9/16" from face*	50

*Uses Steel City® 100 series covers.