











Square boxes and accessories

4" Square old-work box with swing ears and 4" square boxes

4" Square old-work box with swing ears

	Cat. No.	Description	Std. Ctn.
 52171-OW	52171-OW	Metallic 4"-Sq. x 2 ¹ / ₈ "D old-work box with factory-mounted swing ears	25
	OW SWING EAR	Swing ears only (for field installation) with self-threading screws	50 (25 pair)
 OW Swing Ears			

4" Square boxes

						Knockouts (in.)			Std. Ctn.
						Each side Conduit	Each end Conduit	Bottom Conduit	
Cat. No.	Depth (in.)	Capacity (cu. in.)	Clamps	Brackets					
With non-metallic sheathed cable clamps									
 52151 N	1 ¹ / ₂	21.0	C-5	—		2- ¹ / ₂ , 1- ¹ / ₂ , ³ / ₄ E	2	1- ¹ / ₂	50
 52151 MS N* MS bracket for 1 ⁵ / ₈ ", 2 ¹ / ₂ ", 3 ⁵ / ₈ ", 4"	1 ¹ / ₂	21.0	C-5	MS		2- ¹ / ₂ , 1- ¹ / ₂ , ³ / ₄ E	2	1- ¹ / ₂	25
 52151 BN* B bracket mounted flush	1 ¹ / ₂	21.0	C-5	B		2- ¹ / ₂ , 1- ¹ / ₂ , ³ / ₄ E	2	1- ¹ / ₂	25
 52151 VN* SV bracket mounted flush	1 ¹ / ₂	21.0	C-5	SV		2- ¹ / ₂ , 1- ¹ / ₂ , ³ / ₄ E	2	1- ¹ / ₂	25
 52151 CVN* CV bracket mounted flush	1 ¹ / ₂	21.0	C-5	CV		2- ¹ / ₂ , 1- ¹ / ₂ , ³ / ₄ E	2	1- ¹ / ₂	25
 52151 CVNP	1 ¹ / ₂	21.0	C-5	CV		2- ¹ / ₂ , 1- ¹ / ₂ , ³ / ₄ E	2	1- ¹ / ₂	25
 52171 N	2 ¹ / ₈	30.3	C-5	—		2- ¹ / ₂ , 1- ¹ / ₂ , ³ / ₄ E	2	1- ¹ / ₂	25
 52171-VN* SV bracket mounted flush	2 ¹ / ₈	30.3	C-5	SV		2- ¹ / ₂ , 1- ¹ / ₂ , ³ / ₄ E	2	1- ¹ / ₂	25
With conduit KOs									
 52141-1/2	1 ¹ / ₄	18.0	—	—		2- ¹ / ₂	3- ¹ / ₂	5- ¹ / ₂	50
 52151 1/2	1 ¹ / ₂	21.0	—	—		3- ¹ / ₂	3- ¹ / ₂	5- ¹ / ₂	50
 52151-3/4	1 ¹ / ₂	21.0	—	—		2- ³ / ₄	2- ³ / ₄	3- ¹ / ₂ , 2- ³ / ₄	50
 52151 1/2 3/4	1 ¹ / ₂	21.0	—	—		2- ¹ / ₂ , 1- ³ / ₄	2- ¹ / ₂ , 1- ³ / ₄	3- ¹ / ₂ , 2- ³ / ₄	50
 521511234P	1 ¹ / ₂	21.0	—	—		2- ¹ / ₂ , 1- ³ / ₄	2- ¹ / ₂ , 1- ³ / ₄	3- ¹ / ₂ , 2- ³ / ₄	50
 52151-3/4-W	1 ¹ / ₂	21.0	—	—		2- ³ / ₄	2- ³ / ₄	3- ¹ / ₂ , 2- ³ / ₄	50
 52151B1234* B Bracket mounted flush	1 ¹ / ₂	21.0	—	B		2- ¹ / ₂ , 1- ¹ / ₂ , ³ / ₄ E	2- ¹ / ₂ , 1- ³ / ₄ , ³ / ₄ E	3- ¹ / ₂ , 2- ¹ / ₂ , ³ / ₄ E	25
 52151-1/2 & 3/4-EW	1 ¹ / ₂	21.0	—	—		2- ¹ / ₂ , 1- ¹ / ₂ , ³ / ₄ E	2- ¹ / ₂ , 1- ¹ / ₂ , ³ / ₄ E	3- ¹ / ₂ , 2- ¹ / ₂ , ³ / ₄ E	50
 521511234P	1 ¹ / ₂	21.0	—	—		2- ¹ / ₂ , 1- ¹ / ₂ , ³ / ₄ E	2- ¹ / ₂ , 1- ¹ / ₂ , ³ / ₄ E	2- ¹ / ₂ , 2- ¹ / ₂ , ³ / ₄ E	50
 52151-3/4-W	1 ¹ / ₂	21.0	—	—		2- ¹ / ₂ , 1- ¹ / ₂ , ³ / ₄ E	2- ¹ / ₂ , 1- ¹ / ₂ , ³ / ₄ E	2- ¹ / ₂ , 2- ¹ / ₂ , ³ / ₄ E	50
 52151B1234 B Bracket mounted flush	1 ¹ / ₂	21.0	—	—		2- ¹ / ₂ , 1- ¹ / ₂ , ³ / ₄ E	2- ¹ / ₂ , 1- ¹ / ₂ , ³ / ₄ E	2- ¹ / ₂ , 2- ¹ / ₂ , ³ / ₄ E	50
 52151-1/2 & 3/4-EW	1 ¹ / ₂	21.0	—	—		2- ¹ / ₂ , 1- ¹ / ₂ , ³ / ₄ E	2- ¹ / ₂ , 1- ¹ / ₂ , ³ / ₄ E	2- ¹ / ₂ , 2- ¹ / ₂ , ³ / ₄ E	50

* All bracketed boxes come complete with eccentric knockouts. Per UL514A, suitable for use without a bonding jumper in circuits above or below 250 volts. Pigtail wire is #12 AWG insulated, 10¹/₂" long.