

Square boxes and accessories

4" Square extension rings



53151 1/2 3/4



531511234UB**



53151 1/2



53151 3/4



531711234*



53171 1


4" Square extension rings

Cat. No.	Knockouts (in.)		Std. Ctn.
	Each side Conduit	Each end Conduit	
1½" deep — with conduit KOs — 21.0 cubic inch capacity			
53151 1/2	3-1½	3-1½	50
53151 3/4	2-¾	2-¾	25
53151 1/2 3/4	2-1½, 1-¾	2-1½, 1-¾	50
531511234UB**	2-1½, 1-¾, ¾E	2-1½	50
2½" deep — with conduit KOs — 30.3 cubic inch capacity			
531711234*	2-1½, 1-1½, ¾E	2-1½, 1-¾	25
53171 1	2-1	2-1	25


* Per UL 514-A, suitable for use without a bonding jumper in circuits above or below 250 volts.

** ECC, KOs on sides.


4" Square-cut tile wall covers



52 C 49 1/2



52C5011/2-25



52 C 52 1/2

4" Square-cut tile wall covers


Cat. No.	Raised (in.)	Description	Capacity (cu. in.)	Std. Ctn.
For single device – steel				
52 C 49 1/2*	½	–	3.5	50
52-C-49-3/4*	¾	–	5.3	50
52-C-49-1*	1	–	7.0	10
52-C-49-1-1/4	1-¼	–	9.3	10
52C5011/2-25	1-½	–	11.0	25
52C512-25	2	–	14.8	25
For two devices – steel				
52 C 52 1/2	½	Square corners facilitate tile installation	6.0	10
52-C-52-3/4	¾		9.0	10
52-C-52-1	1		12.5	10
52-C-52-1-1/4	1-¾		15.5	10
52 C 53 1 1/2	1-½		19.0	10
52 C 54 2	2-¾		25.5	10

* Drawn style.

4" Square covers



52 C 1



52 C 3 1



52 C 6

4" Square covers



Cat. No.	Raised (in.)	Description	Capacity (cu. in.)	Std. Ctn.
52 C 1	–	Flat, blank	–	100
52-C-3-25	⅝	Center blanked with tapped ears on 2¾" centers	4.3	25
52-C-3-1/2-25	½		3.5	25
52-C-3-3/4	¾	Center blanked with tapped ears on 22¾" centers	4.3	25
52 C 3 1	1		5.8	25
52-C-3-1-1/4	1⅛		7.3	25
52 C 6	–	Flat, with ½" KO	–	100

4" Square device covers




52 C 16




52 C 19



52 C 21



52 C 0




52 C 10



52 C 14



52-C-36



52 C 00



52-C-17-25



52 C 21

4" Square-cut tile wall covers

Cat. No.	Raised (in.)	Description	Capacity (cu. in.)	Std. Ctn.
For single device – steel				
52 C 0	–	Flat	–	25
52 C 62	¼	Keyed for plaster	1.5	25
52 C 10	¼	Offset, keyed for plaster	1.0	25
52 C 13	½	–	3.0	50
52 C 14	¾	–	5.0	50
52 C 14 5/8	⅝	–	4.0	50
52 C 15	1	–	7.0	25
52 C 16	1¼	–	8.3	25
52-C-36	¼	For drywall construction	1.0	25
For two devices				
52 C 00	–	Flat	–	25
52C20-25	¼	–	2.3	25
52-C-17-25	½	–	6.3	25
52 C 18	¾	–	9.0	25
52-C-18-5/8-25	⅝	For drywall construction	7.3	25
52 C 19	1	–	12.0	25
52 C 21	1¼	–	15.0	25
52 C 37	⅛	–	2.3	25
52 C 53 1 1/2	1-½	–	19.0	10
52 C 54 2	2-¾	–	25.5	10