



Square boxes and accessories


4¹¹/₁₆" Square surface and device covers




RSL 2




RSL 4




RSL 5




RSL 8




RSL 9




RSL 11




RSL 12




RSL 13




RSL 14




RSL 15




RSL 16



RSL 17




RSL 18



RSL 19

4¹¹/₁₆" Square surface covers

Cat. No.	Depth (in.)	Capacity (cu. in.)	Dia. Hole (in.)	Description	Std. Ctn.
RSL 2	1/2	7.5	—	For one toggle switch and one duplex flush receptacle	10
RSL 4	1/2	7.5	1 ¹¹ / ₃₂	For one 4-wire twist-lock single receptacle	10
RSL 5	1/2	7.5	—	For two toggle switches	10
RSL 8	1/2	7.5	—	For two duplex, flush receptacles	10
RSL 9	1/2	7.5	1 ⁵ / ₃₂	For one toggle switch	10
RSL 11	1/2	7.5	1 ⁵⁵ / ₆₄	For one single, flush receptacle	10
RSL 12	1/2	7.5	—	For one duplex, flush receptacle	10
RSL 13	1/2	7.5	2 ⁵ / ₃₂	For one 30A to 50A dryer or range receptacle	10
RSL 14	1/2	7.5	2 ⁵ / ₃₂	—	10
RSL 15	1/2	7.5	1 ³ / ₄	For #3330-30A 250 V twist-lock receptacle	10
RSL 16	1/2	7.5	—	For one ground fault receptacle	10
RSL 17	1/2	7.5	—	For two ground fault receptacles	10
RSL 18	1/2	7.5	—	For one ground fault receptacle and one toggle switch	10
RSL 19	1/2	7.5	—	For one ground fault receptacle and one duplex receptacle	10



72 C 13




72 C 15



72 C 14



72 C 17



72 C 21

4¹¹/₁₆" Square device covers

Cat. No.	Depth (in.)	Capacity (cu. in.)	Std. Ctn.
For single device			
72 C 62	1/4	1.0	25
72 C 13	1/2	3.0	25
72 C 14	3/4	5.0	25
72 C 14 5/8	5/8	4.0	25
72 C 15	1	7.0	10
72 C 16	1 ¹ / ₄	8.3	10
For two devices			
72 C 17	1/2	6.3	25
72 C 18	3/4	9.0	25
72 C 18 5/8	5/8	7.5	25
72 C 19	1	12.0	25
72 C 21	1 ¹ / ₄	15.0	25