


Rigid conduit/IMC fittings

Set-screw couplings




Set-screw couplings – steel (concrete tight) when taped – zinc plated



Cat. No.	Conduit Size (in.)	Dimensions (in.)		Std. Ctn.
		A	B	
Die-cast zinc flexible metal conduit to EMT				
HK-101	1/2	1 1/8	2 ¹³ /32	100
HK-102	3/4	1 3/8	2 ¹⁷ /32	50
HK-103	1	5/8	2 ¹¹ /16	50
HK-104	1 1/4	2	2 ²⁵ /32	25
HK-105	1 1/2	2 1/4	3 ¹¹ /64	25
HK-106	2	2 3/4	3 ¹³ /32	20
HK-107	2 1/2	3 7/16	3 ²⁹ /32	10
HK-108	3	4 1/16	4 ⁵ /32	5
HK-109	3 1/2	4 9/16	4 7/8	5
HK-110	4	5 1/16	5 3/8	5


Two set screws starting at 2".
UL File No. E-23018.

Rigid connectors – set-screw type




Rigid connectors – set-screw type – die-cast zinc

Cat. No.	Trade Size (in.)	Dimensions (in.)		Std. Ctn.
		A	B	
HK-203	1	1.54	0.49	100
HK-802	3/4	1.44	0.45	250
HK-803	1	1.54	0.49	100



Cat. No.	Trade Size (in.)	Dimensions (in.)		Std. Ctn.
		A	B	
HK-201	1/2	1.77	1.09	250
HK-203	1	2.29	1.61	100

90° short-radius elbows




90° short-radius elbows – die-cast zinc



Cat. No.	Size (in.)	Dimensions (in.)		SHF. CTF./ Ship Qty.
		A	B	
HL-202-SC	3/4	1.17	1.04	25/250

Use: To join rigid or IMC conduit at right angles where lack of room prevents using a standard sweep elbow or to terminate a run of rigid or IMC conduit at a box.
UL® Listing E37148.

Three-piece couplings



Features and benefits:

- 1/2"–2 1/2" – steel
- 2 1/2"–6" – malleable iron


Three-piece couplings – zinc-plated



Cat. No.	Conduit Size (in.)	Dimensions (in.)		SHF. CTF./ Ship Qty.
		A (Assembled)	B	
EK 401	1/2	1 1/16	1 1/8	100
EK 402	3/4	1 1/8	1 11/32	50
EK 403	1	1 3/8	1 5/8	25
EK 404	1 1/4	1 21/32	2 5/32	25
EK 405	1 1/2	1 7/8	2 23/32	25
EK 406	2	2	3 33/64	20
EK 407	2 1/2	2 1/2	3 29/64	10
EK 408	3	3 3/8	4 23/32	6
EK 409	3 1/2	3 5/8	5 5/32	5
EK 410	4	3 29/32	5 29/32	5
EK 411	5	4 5/16	7	1

One set screw or two. Two set screws starting at 2" trade size.
Suggested use — rigid conduit only.
UL File No. E-23018 – 1/2"-1 1/4".

Rigid couplings – three-piece type



Rigid couplings – three-piece type – die-cast zinc

Cat. No.	Conduit Size (in.)	Dimensions (in.)		SHF. CTF./ Ship Qty.
		A (Assembled)	B	
EK201	1/2	1.39	1.31	100
EK 202	3/4	1.53	1.58	50