


Rigid conduit/IMC fittings

Rigid to box with gasket

Rigid to box with gasket – die-cast zinc




Cat. No.	Conduit Size (in.)	Dimensions (in.)		SHF. CTF./ Ship Qty.
		A (Assembled)	B	
HL-611	1/2	1.31	1.09	100
HL-612	3/4	1.47	1.29	50

UL File No. E-23018.

Pull corner elbows

Pull corner elbows – die-cast zinc



Cat. No.	Conduit Size (in.)	Dimensions (in.)		Std. Ctn.
		A	B	
HL-601	1/2	1.31	1.10	100
HL-602	3/4	1.60	1.24	50
HL-603	1	1.95	1.59	25
HL-604	1 1/4	2.26	1.97	30

UL File No. E-23018.

The T&B® hub with insulated throat*

Features and benefits:

- The T&B Hub with sealing ring that will not fall out
- Provides superior sealing for exceptional watertight performance
- Color blue is a registered trademark of Thomas & Betts Corporation

The T&B® hub with insulated throat* – die-cast zinc



Cat. No.	Conduit Size (in.)	Std. Ctn.
Die-cast zinc flexible metal conduit to EMT		
H050-SC	1/2	100
H075-SC	3/4	100
H100-SC	1	25
H125-SC	1 1/4	25
H150-SC	1 1/2	10
H200-SC	2	5
H250-SC	2 1/2	5
H300-SC	3	2
H350-SC	3 1/2	2
H400-SC	4	1
H500-SC	5	1
H600-SC	6	1

*Available in nickel-chrome plating or with PVC coating.
Consult customer service for price and delivery.
UL File No. E-23018.