

Electrical metallic tubing (EMT) fittings

Set-screw connectors and couplings



Set-screw connectors – steel – zinc plated



"A" Cat. No.	Conduit Size (in.)	Inner Pack	Outer Pack
Non-insulated			
TC121A	1/2	50	500
TC122A	3/4	50	250
TC123A	1	25	100
TC124A	1 1/4	–	25
TC125A	1 1/2	–	25
TC126A	2	–	25
TC127A	2 1/2	–	10
TC128A	3	–	5
TC129A	3 1/2	–	5
TC1210A	4	–	5
TC121A-FA	1/2	50	500
TC122A-FA	3/4	50	250
TC123A-FA	1	25	100

UL File No. E-16592.
FA — Fire Alarm.

Features and benefits:

- Concrete tight when taped



"A" Cat. No.	Conduit Size (in.)	Inner Pack	Outer Pack
Insulated			
TC-721A	1/2	50	500
TC722A	3/4	50	250
TC-723A	1	25	100
TC724A	1 1/4	–	25
TC725A	1 1/2	–	25
TC726A	2	–	25
TC727A	2 1/2	–	10
TC728A	3	–	5
TC729A	3 1/2	–	5
TC7210A	4	–	5
TC721A-FA	1/2	50	500
TC722A-FA	3/4	50	250
TC723A-FA	1	25	100

UL File No. E-16592.
FA — Fire Alarm.



Set-screw couplings – steel – zinc plated



"A" Cat. No.	Conduit Size (in.)	Inner Pack	Outer Pack
TK121A	1/2	50	500
TK122A	3/4	50	250
TK123A	1	25	100
TK124A	1 1/4	–	25
TK125A	1 1/2	–	25
TK126A	2	–	25
TK127A	2 1/2	–	10

UL File No. E-16592.

Features and benefits:

- Concrete tight when taped
- Fire Alarm (FA) painted red for fire alarm identification



"A" Cat. No.	Conduit Size (in.)	Inner Pack	Outer Pack
TK128A	3	–	5
TK129A	3 1/2	–	5
TK1210A	4	–	5
TK121A-FA	1/2	50	500
TK122A-FA	3/4	50	250
TK123A-FA	1	25	100

UL File No. E-16592.