

Electrical metallic tubing (EMT) fittings

Compression connectors and couplings



Steel City® Raintight EMT compression fittings feature a distinctive design and a vibrant gold gland nut, enabling inspectors to visually inspect conformance from a distance. There's no close up inspection required!

Features and benefits:

- ½"-4" Concrete tight when taped
- RT - Raintight

Compression connectors – steel – zinc plated



"A" Cat. No.	Conduit Size (in.)	Inner Pack	Outer Pack
Non-insulated			
TC111A	½	50	500
TC112A	¾	50	250
TC113A	1	25	100
TC114A*	1¼	–	25
TC115A*	1½	–	25
TC116A*	2	–	25
TC117A	2½	–	10
TC118A	3	–	5
TC119A	3½	–	5
TC1110A	4	–	5
TC111A-RT	½	50	500
TC112A-RT	¾	50	250
TC113A-RT	1	25	100
TC114A-RT*	1¼	–	25
TC115A-RT*	1½	–	25
TC116A-RT*	2	–	25
TC117A-RT	2½	–	10
TC118A-RT	3	–	5
TC119A-RT	3½	–	5
TC1110A-RT	4	–	5

UL File No. E-16592.

*O-rings are supplied..



"A" Cat. No.	Conduit Size (in.)	Inner Pack	Outer Pack
Insulated			
TC711A	½	50	500
TC712A	¾	50	250
TC713A	1	25	100
TC714A	1¼	–	25
TC715A	1½	–	25
TC716A	2	–	25
TC717A	2½	–	10
TC718A	3	–	5
TC719A	3½	–	5
TC7110A	4	–	5
TC711A-RT	½	50	500
TC712A-RT	¾	50	250
TC713A-RT	1	25	100
TC714A-RT*	1¼	–	25
TC715A-RT*	1½	–	25
TC716A-RT*	2	–	25
TC717A-RT	2½	–	10
TC718A-RT	3	–	5
TC719A-RT	3½	–	5
TC7110A-RT	4	–	5

UL File No. E-16592.



Steel City® Raintight EMT compression fittings feature a distinctive design and a vibrant gold gland nut, enabling inspectors to visually inspect conformance from a distance. There's no close up inspection required!

Features and benefits:

- ½"-4" Concrete tight when taped
- RT - Raintight

Compression couplings – steel – zinc plated



"A" Cat. No.	Conduit Size (in.)	Inner Pack	Outer Pack
TK111A	½	50	250
TK112A	¾	50	250
TK113A	1	25	100
TK114A	1¼	–	25
TK115A	1½	–	25
TK116A	2	–	25
TK117A	2½	–	10
TK118A	3	–	5
TK119A	3½	–	5
TK1110A	4	–	5

UL File No. E-16592.



"A" Cat. No.	Conduit Size (in.)	Inner Pack	Outer Pack
TK111A-RT	½	50	250
TK112A-RT	¾	50	250
TK113A-RT	1	25	100
TK114A-RT	1¼	–	25
TK115A-RT	1½	–	25
TK116A-RT	2	–	25
TK117A-RT	2½	–	10
TK118A-RT	3	–	5
TK119A-RT	3½	–	5
TK1110A-RT	4	–	5

UL File No. E-16592.