

Electrical metallic tubing (EMT) fittings

Offset compression connectors




Offset compression connectors – die-cast zinc



Cat. No.	Offset (in.)	Conduit Size (in.)	Dimensions (in.)		Std. Ctn.
			A	B	
TO-211SC	3/8	1/2	2 ¹³ / ₆₄	1	200

UL File No. E-16592.

Capped corner couplings



Features and benefits:

- Concrete tight when taped




Capped corner couplings – die-cast zinc

Cat. No.	Conduit Size (in.)	Dimensions (in.)		Std. Ctn.
		A	B	
TL-291	1/2	1.81	1.00	100
TL-292	3/4	2.00	1.25	50

UL File No. E-16592.
CSA File No. LR-12798.

Compression couplings



Features and benefits:

- 1/2"-4" Concrete tight




Compression couplings – die-cast zinc

Cat. No.	Conduit Size (in.)	Dimensions (in.)		Std. Ctn.
		A	B	
TK-211-SC	1/2	1 1/2	1 3/32	500
TK-212-SC	3/4	1 5/8	1 5/16	250
TK-213-SC	1	1 7/8	1 45/64	200
TK-214-SC	1 1/4	1 13/16	2 3/32	100
TK-215-SC	1 1/2	2 9/32	2 21/64	40
TK-216-SC	2	2 11/32	2 29/32	20
TK-217-SC	2 1/2	3 13/64	3 11/64	12
TK-218-SC	3	3 7/32	4 1/2	12
TK-219-SC	3 1/2	3 9/64	5 1/16	10
TK-2110-SC	4	3 3/16	4 41/64	6

UL File No. E-16592 – 1/2"-4".
CSA File No. LR-12798 – 1/2"-1 1/4", 2 1/2"-4".

Set-screw connectors



Features and benefits:

- Concrete tight when taped




Set-screw connectors – die-cast zinc

Cat. No.	Conduit Size (in.)	A (in.)		B (in.)	Std. Ctn.
		TC-221 Series	TC-821 Series		
Non-insulated					
TC-221-SC	1/2	1 ⁵ /32	1 ¹⁷ /64	1 ⁵ /16	500
TC-222-SC	3/4	1 ¹³ /32	1 ³³ /64	1 ⁵ /32	250
TC-223-SC	1	1 ⁹ /16	1 ²¹ /32	1 ²⁷ /64	200
TC-224-SC	1 1/4	1 ¹⁵ /16	2 ¹ /32	1 ¹³ /16	100
TC-225-SC	1 1/2	2 ⁹ /32	2 ³ /8	2 ³ /64	40
TC-226-SC	2	2 ³³ /64	2 ³⁹ /64	2 ¹⁷ /32	20
TC-227-SC	2 1/2	3 ³ /16	3 ⁹ /32	3 ¹⁹ /64	12
TC-228-SC	3	3 ²⁵ /64	3 ³¹ /64	4 ¹ /16	12
TC-229-SC	3 1/2	3 ³¹ /64	3 ¹⁹ /32	4 ¹⁷ /32	10
TC-2210-SC	4	3 ⁴⁷ /64	3 ⁵³ /64	5 ¹ /16	6
Insulated					
TC-821-SC	1/2	1 ⁵ /32	1 ¹⁷ /64	1 ⁵ /16	500
TC-822-SC	3/4	1 ¹³ /32	1 ³³ /64	1 ⁵ /32	250
TC-823-SC	1	1 ⁹ /16	1 ²¹ /32	1 ²⁷ /64	200
TC-824-SC	1 1/4	1 ¹⁵ /16	2 ¹ /32	1 ¹³ /16	100
TC-825-SC	1 1/2	2 ⁹ /32	2 ³ /8	2 ³ /64	40
TC-826-SC	2	2 ³³ /64	2 ³⁹ /64	2 ¹⁷ /32	20
TC-827-SC	2 1/2	3 ³ /16	3 ⁹ /32	3 ¹⁹ /64	12
TC-828-SC	3	3 ²⁵ /64	3 ³¹ /64	4 ¹ /16	12
TC-829-SC	3 1/2	3 ³¹ /64	3 ¹⁹ /32	4 ¹⁷ /32	10
TC-8210-SC	4	3 ⁴⁷ /64	3 ⁵³ /64	5 ¹ /16	6

UL File No. E-16592 – 1/2"-4".
UL File No. E-23018 – 2 1/2"-4".
CSA File No. LR-12798 – 1/2"-1", 2 1/2"-4".

Offset set-screw connectors



Features and benefits:

- Concrete tight when taped



Offset set-screw connectors – die-cast zinc

Cat. No.	Offset (in.)	Conduit Size (in.)	Dimensions (in.)			Std. Ctn.
			A	B	C	
TO 221	3/8	1/2	2.00	0.90	0.37	100
TO 222	3/4	3/4	2.98	1.16	0.25	100
TO-223	3/4	1	3.15	1.42	0.75	100

UL File No. E-16592.
CSA File No. LR-18130M57.