




Beam and Purlin clamps

Beam clamps



- Supports threaded rod, threaded bridle rings and electrical boxes
- Bright zinc plating
- Supports 100 lbs. static load limit


Beam clamps – Malleable iron, electro-plated finish

	Cat. no.	Fig no.	Description	Static load limit (lbs)	STD CTN
Fig. 1 	BC1-TB	1	Steel beam clamp, 1/4"-20 threaded openings, fits flanges up to 5/8" thick	75	50
	BC2-TB	1	Steel beam clamp, 5/16"-18 threaded openings, fits flanges up to 3/4" thick	320	50
	510	2	Malleable iron beam clamp, 1/4"-20 threaded openings, fits flanges up to 5/8" thick	250	100
	511-SC	2	Malleable iron beam clamp, 10-24 threaded openings, fits flanges up to 5/8" thick	250	100
Fig. 2 	500-SC	2	Malleable iron beam clamp, 1/4"-20 threaded openings, fits flanges up to 1 5/16" thick	250	50
	509	2	Malleable iron beam clamp, 10-24 threaded openings, fits flanges up to 1 5/16" thick	150	100
	501	2	Malleable iron beam clamp, 1 5/16"-18 threaded openings, fits flanges up to 7/8" thick	500	50
	502	2	Malleable iron beam clamp, 3/8"-16 threaded openings, fits flanges up to 1" thick	750	25
	503-SC	2	Malleable iron beam clamp, 1/2"-13 threaded openings, fits flanges up to 1" thick	1,250	20
	507	2	Malleable iron beam clamp, 1/2"-13 threaded openings, fits flanges up to 1 3/8" thick	1,250	20
	508	2	Malleable iron beam clamp, 1/2"-13 threaded openings, fits flanges up to 2 1/8" thick	1,250	10

Safety Factor of 3. Load ratings based on bottom hole of beam clamp. CSA File No. LR-63683.

BC1-TB & BC2-TB

Cat. no.	Size (in)	Tapped	Dimensions (in)				STD CTN
			A	B	C	D	
BC1-TB	1	1/4-20	1 11/16	1 3/8	5/8	1 3/16	250
BC2-TB	2 15/16	3/8-16	2 1/8	2 1/16	3/4	1 11/16	25



Material: Steel. Finish: Zinc plated.