

Beam and Purlin clamps

Beam clamps

Beam clamps

	Cat. no.	Fig no.	O.D. of conduit or pipe (in)	OM. conduit or pipe size (in)	STD CTN
Fig. 1	RCS Clamp — Steel				
	RCS-1/2	1	.840	1/2	50
	RCS-3/4	1	1.050	3/4	50
	RCS-1	1	1.315	1	100
	RCS-1-1/4	1	1.660	1 1/4	100
	RCS-1-1/2	1	1.900	2	100
Fig. 2	RCS-2	1	2.375	2	100
	RC Clamp — Malleable Iron				
	RC-3/8	1	.675	3/8	50
	RC-1/2	1	.840	1/2	50
	RC-3/4	1	1.050	3/4	50
	RC-1	1	1.315	1	100
	RC-1-1/4	1	1.660	1 1/4	100
	RC-1-1/2	1	1.900	1 1/2	100
	RC-2-SC	1	2.375	2	100
	RC-2-1/2	1	2.875	2 1/2	100
	RC-3	1	3.500	3	100
	RC-3-1/2	1	4.000	3 1/2	100
	RC-4-SC	1	4.500	4	100
	EC Clamp — Malleable Iron				
	EC 1/2	2	.840	1/2	50
	EC-3/4	2	1.050	3/4	50
	EC-1	2	1.315	1	100
	EC-1-1/4	2	1.660	1 1/4	100
	EC-1-1/2	2	1.900	1 1/2	100
	EC-2	2	2.375	2	100
	EC-2-1/2	2	2.875	2 1/2	100
	EC-3	2	3.500	3	100
	PC Clamp — Malleable Iron				
	PC-3/8	3	.675	3/8	50
	PC 1/2	3	.840	1/2	50
	PC-3/4	3	1.050	3/4	50
	PC-1	3	1.315	1	100
	PC-1-1/4	3	1.660	1 1/4	100
	PC-1-1/2	3	1.900	1 1/2	100
	PC-2	3	2.375	2	100
	PC-2-1/2	3	2.875	2 1/2	100
	PC-3	3	3.500	3	100
	PC-3-1/2	3	4.000	3 1/2	100
	PC-4	3	4.500	4	100