


Meets and surpasses NEC® requirements!

Insulated Throat Fittings

- Steel or malleable iron (steel through 1½")
- Exceeds NEC 373-6C requirements for protection of ungrounded connectors at entrance to raceways, pull boxes and junctions
- Recognizable by distinctive trademarked blue insulating liner in throat
- Reduces wire pulling effort by as much as 50%
- Temperature rating of 105° C
- Look for the unique T&B blue color, ensuring the highest quality fitting



CAT. NO.		SIZE	DIMENSIONS (IN.)	
STL. OR M.I.	ALUM.		A	B
1222	1222AL	½"	1½"	29/64"
1223	1223AL	¾"	1½"	31/64"
1224	1224AL	1"	1¾"	1½"
1225	1225AL	1¼"	1½"	21/32"
1226	1226AL	1½"	2¾"	23/32"
1227	1227AL	2"	2½"	¾"
1228	1228AL	2½"	3¾"	1½"
1229	1229AL	3"	3¾"	5/8"
1230	1230AL	3½"	4¾"	1½"
1231	1231AL	4"	4¾"	1½"
1232†	1232AL†	4½"	—	—
586	586AL	5"	5¾"	1½"
587	587AL	6"	7¾"	1½"


† Not CSA Certified

Catalog series 1222 thru 1232, 586 and 587 are available in aluminum. Add suffix AL to Cat. No. The aluminum series fittings are not CSA certified.

Locknut-type base improves bonding and resists loosening under vibration.

Metallic Bushings

- Aluminum, steel or malleable iron (steel through 1½")
- Smoothly rounded shoulder covers end of conduit
- Broad flange covers knockout hole
- High ribs for easy tightening with fingers or with wrench
- ½" to 1½" sizes, formed in steel, feature extra-smooth shoulders



CAT. NO.			DIMENSIONS (IN.)	
STL. OR M.I.	ALUM.	SIZE	A	B
122	122AL	½"	1½"	13/32"
123	123AL*	¾"	1¼"	7/16"
124	124AL**	1"	1¾"	1/2"
125-TB	125AL	1¼"	1¾"	9/16"
126	126AL	1½"	2¾"	19/32"
127	127AL	2"	2¾"	5/8"
128	128AL	2½"	3¾"	3/4"
129	129AL	3"	3¾"	13/16"
130-TB	130AL	3½"	4¾"	15/16"
131-TB	131AL	4"	4¾"	1"
132-TB	—	4½"	5¾"	1¼"
133-TB	133AL	5"	6"	1½"
134-TB	134AL	6"	7¼"	1½"

* Not UL Listed or CSA Certified

UL File No. E-23018


** Not CSA Certified

CSA File No. 2884

Available with DURA-PLATE® Finish.

Perfect threads for easy thread-on!

Plastic Insulating Bushings



All Plastic Insulating Bushings

- Impact-resistant plastic insulation
- Ribbed for easy, secure gripping
- UL Listed 105° C



CAT. NO.	SIZE	DIMENSIONS (IN.)	
		A	B
222-TB	½"	1⅞	¾
223-TB	¾"	1⅞	1⅞
224	1"	1⅞	¾
225-TB	1¼"	1⅞	¾
226	1½"	2⅞	¾
227	2"	2⅞	⅝
228-TB	2½"	3⅞	¾
229-TB	3"	4⅞	¾
230-TB	3½"	4⅞	⅞
231	4"	5⅞	⅞
232	4½"	5⅞	1
233	5"	6⅞	1
234	6"	7⅞	1

UL Rated flame retardant 94V-1