

Rigid and Intermediate Metal Conduit Fittings



Made from flame-retardant, non-dripping thermoplastic, UL rated 105° C!

Knockout Plugs

Application

- To plug unused knockout openings in a box or enclosure

Features

- One-piece construction designed to snap in place
- High impact strength self-extinguishing non-dripping (per UL-94) thermoplastic construction

Standard Material

Thermoplastic rated for 105° C (221° F) application

Standard Finish


As molded

Range

.875" through 2.469" Nominal Diameter

Knockout opening (½" through 2" trade size knockouts)

1451 Series



105° C rated by UL Made from flame retardant, non-dripping thermoplastic.



Wall thickness of box or enclosure

.095" max. up to 1" trade size

.140" max. through 2" trade size.

Listings/Compliances

UL (UL File No. E13938)

CSA (LR589)

UL 514B

NFPA 70

CAT. NO.	SIZE	DIMENSIONS (IN.)	
		A	B
1451	½"	1.060	.400
1452	¾"	1.300	.400
1453	1"	1.590	.400
1454	1¼"	1.860	.450
1455	1½"	2.240	.570
1456	2"	2.740	.570

Wall thickness of electrical box .095 max.

Meets Coast Guard Regulation CB293.

UL File No. E-13938 CSA File No. 4484

Eliminates need for separate capped bushing or steel penny and bushing!

Plug, Conduit, Connectors (Push-Penny® Plugs)

Application

- To plug open end of conduit or connector in order to prevent ingress of trash, dirt or moisture during construction and remodeling
- Just push into place
- Pressure holds plug fast against internal surface of fitting or raceway
- Made of flexible plastic

Features

- Wide range of applications; can be used with rigid metal conduit, intermediate metal conduit, electrical metallic tubing, all connectors and all bushings
- Designed to stand up to normal handling and is functionally unaffected by moisture
- Economically seal out grout and plaster from any fitting or raceway conforming to CSA dimensional tolerances

Standard Material

Polyethylene

Standard Finish

As molded

Listings/Compliances

CSA (LR2884, LR4484)

UL 514B

CSA C22.2 No. 18

NFPA 70

NEMA FB1



CAT. NO.	SIZE
1470	½"
1471	¾"
1472	1"
1473	1¼"
1474	1½"
1475	2"
1476*	2½"
1477*	3"
1478*	3½"
1479*	4"

*Not CSA Certified.


CSA File No. 2884

UL not applicable.

Made to fit any bushing!

Pennies — Steel

- Used under a bushing to seal end of conduit during construction
- Completely salvageable



CAT. NO.	SIZE
815-TB	½"
816	¾"
817	1"
818	1¼"
819	1½"
820	2"

CAT. NO.	SIZE
821	2½"
822	3"
824	3½"
823	4"

UL not applicable.
CSA File No. 2884