


MC and AC Cable Fittings



Fits every size of armored cable, metal-clad cable and flexible metal conduit!

Squeeze Connectors — Straight



- Malleable iron or steel construction
- Catalog Nos. 252, 253-TB, 254-TB and 255 are steel
- Add "I" suffix for insulated throat

CAT. NO.	INS. CAT. NO.	CABLE OPENING (IN.)		TRADE SIZE	K.O. SIZE	DIMENSIONS (IN.)		
		MAX.	MIN.			A†	B	C
252***	—	.531	.437	5/16"	3/8"	13/16	25/32	11/32
253-TB***†	253-I-TB***†	.585	.455	3/8"	1/2"	31/32	113/64	5/8
254-TB	254-I-TB	.938	.812	1/2"	1/2"	17/32	13/8	13/32
255	255-I	1.094	.938	3/4"	3/4"	1 1/4	1 17/32	7/16
256	256-I	1.375	1.250	1"	1"	1 19/32	1 5/8	1/2
257***	257-I***	1.656	1.500	1 1/4"	1 1/4"	1 5/8	1 23/32	17/32
258***	258-I***	1.875	1.688	1 1/2"	1 1/2"	2 1/4	1 7/16	9/16
259***	259-I***	2.500	2.313	2"	2"	2 31/32	2 5/8	1 1/16
249***	249-I***	3.062	2.812	2 1/2"	2 1/2"	3 5/16	2 11/16	3/4
277***	277-I***	3.563	3.312	3"	3"	3 13/16	2 7/8	3/4
278-TB***†	278-I-TB***†	4.370	3.200	3 1/2"	3 1/2"	6 5/8	5 1/4	1 1/16
281-TB***†	281-I-TB***†	4.600	3.500	4"	4"	7 1/4	5 3/4	1 5/8

** UL Listed for armored cable only. Fitting material steel.

*** UL Listed for flexible metal conduit only.

† Approximate dimension with screw at minimum height.

†† cULus Certified


.485"–.660" cable opening range for 253-I-TB.

UL File No. E 23018

CSA File No. 2884

Only two screws to tighten!

Squeeze Connectors — 90° Angle



- Cap lifts off simply by loosening screws partway
- 3/8" and 1/2" sizes made of steel
- 3/4" and larger sizes made of malleable iron
- Add "I" suffix for insulated throat

CAT. NO.	INS. CAT. NO.	CABLE OPENING (IN.)		TRADE SIZE	K.O. SIZE	DIMENSIONS (IN.)		
		MAX.	MIN.			A†	B	C
266-TB	266-I-TB	.656	.406	3/8"	1/2"	1 1/2	1 13/32	1 7/16
272**	272-I**	.812	.688	3/8"	1/2"	1 1/16	1 1/8	—
268-TB	268-I-TB	.937	.813	1/2"	1/2"	1 11/16	1 13/16	1 1/8
279	279-I	1.000	.875	3/4"	3/4"	1 13/16	2 1/16	1 13/16
270	270-I	1.125	1.000	3/4"	3/4"	1 5/8	1 3/4	1 13/16
273-TB	273-I-TB	1.406	1.187	1"	1"	2 3/8	2 1/32	2 1/16
274***	274-I***	1.656	1.375	1 1/4"	1 1/4"	3	3	3
275***	275-I***	1.875	1.625	1 1/2"	1 1/2"	3 3/8	3 1/16	4
276***	276-I***	2.500	2.125	2"	2"	4 1/2	3 13/16	4 7/8
282-TB***†	282-I-TB***†	3.100	2.520	2 1/2"	2 1/2"	4 5/16	5 1/16	7 9/16
283-TB***†	283-I-TB***†	3.640	3.100	3"	3"	5 1/16	6 1/16	8 13/16
284-TB***†	284-I-TB***†	4.220	3.700	3 1/2"	3 1/2"	6 13/16	8 1/16	11 1/4
285-TB***†	285-I-TB***†	4.600	4.100	4"	4"	7 1/4	8 3/8	12 3/8

** UL Listed for armored cable only.

*** UL Listed for flexible metal conduit only.

† Approximate dimension with screw at minimum height.


†† cULus Certified

UL File No. E23018

CSA File No. 2884

Fast and easy installation — simply loosen screws partway to lift off cap!

Squeeze Connectors — 45° Angle



- 3/8" and 1/2" sizes made of steel
- 3/4" size made of malleable iron
- Add "I" suffix for insulated throat

CAT. NO.	INS. CAT. NO.	CABLE OPENING (IN.)		TRADE SIZE	K.O. SIZE	DIMENSIONS (IN.)		
		MAX.	MIN.			A†	B	C
265	265-I	.656	.406	3/8"	1/2"	1 17/32	1 5/32	1 1/8
267	267-I	.937	.813	1/2"	1/2"	1 23/32	1 1/2	1 1/4
269	269-I	1.125	1.000	3/4"	3/4"	2	1 7/32	1 9/16

UL File No. E-23018

CSA File No. 2884

UL Listed for armored cable and flexible metal conduit.

† Approximate dimension with screw at minimum height.