


Conduit bodies and covers

Mogul conduit outlet bodies

Application

- Act as pull outlets for conductors that are stiff, due to large size or type of insulation
- Provide the longer openings needed when pulling large conductors
- Prevent sharp bends and kinks in large conductors (protects insulation during installation)
- Provide ample openings for splices and taps
- Provide access to wiring for maintenance and future system changes



BC mogul series (cover and gasket included)

Features

- Long openings
- Provision for easy bends
- Tapered tapped hubs with integral bushings
- Stainless steel cover screws
- Covers and gaskets included

Standard materials

- Class 30 gray iron alloy

Standard finishes

- Electrogalvanized and aluminum acrylic paint

Listings/compliances

- UL Standard: 514B
- Fed. Spec.: W-C-586D
- CSA Standard: C22.2 No.18
- UL listed for wet locations

Note: See NEC® 370-28 (a) (1) and (2) for pull length and bending space requirements applicable to BC, BLB and BUB series moguls.



	Cat. no.	Hub size (in.)	Dimensions (in.)					Cu. in.
			A	B	C	D	E	
Diagrams 	BC3-TB	1	9.56	1.88	2.25	7.84	6	20.0
	BC4-TB	1¼	9.56	2.31	2.25	7.84	6	25.0
	BC5-TB	1½	13.75	2.56	3	11.45	10	60.0
	BC6-TB	2	13.75	3.31	3	11.45	10	78.0
	BC7-TB	2½	18.38	3.63	4.25	15.61	15	180.0
	BC8-TB	3	18.38	4.38	4.25	15.82	15	225.0
	BC10-TB	4	23.75	5.38	5.25	20.50	20	460.0



BLB mogul series (cover and gasket included)



	Cat. no.	Hub size (in.)	Dimensions (in.)					Cu. in.
			A	B	C	D	E	
Diagrams 	BLB3-TB	1	8.66	2.80	2.25	6.92	6	20.0
	BLB4-TB	1¼	8.66	2.70	2.25	6.70	6	25.0
	BLB5-TB	1½	12.58	2.56	3	10.36	10	62.0
	BLB6-TB	2	12.58	4.16	3	10.13	10	78.0
	BLB7-TB	2½	16.94	5.10	4.25	13.89	15	170.0
	BLB8-TB	3	16.94	5.81	4.25	13.59	15	210.0
	BLB9-TB	3½	22.16	6.50	5.25	18.32	20	410.0
	BLB10-TB	4	22.16	7.00	5.25	18.06	20	460.0