


Liquidtight flexible metal conduit fittings

PG fittings

Fittings for liquidtight flexible metal conduit with metric threads of PG form (DIN 40430).

PG metric thread liquidtight fittings



	Cat. no.	Flexible conduit size (in.)	Metric PG thread	Dimensions (mm)		
				A	B	C
	Nylon-insulated straight fittings					
	7330**	¼	9	36	21	12
	7360**	5/16	9	36	26	12
	7361*	3/8	11	40	29	14
	7362*	3/8	13.5	40	29	14
	7363*	½	16	41	35	14
	7364*	¾	21	43	42	14
	7365	1	29	56	47	19
	7366	1¼	36	67	58	21
7367	1½	42	72	69	21	
7368	2	48	81	83	21	
	Nylon-insulated 45° angle fittings					
	7341	3/8	11	27	29	14
	7342	3/8	13.5	27	29	14
	7343	½	16	30	35	14
	7344-TB	¾	21	34	42	14
	7345	1	29	44	47	19
	7346	1¼	36	51	58	19
	7347	1½	42	60	69	21
	7348-TB	2	48	73	76	24
	Nylon-insulated 90° angle fittings					
	7351	3/8	11	37	29	14
	7352	3/8	13.5	37	29	14
	7353	½	16	40	35	14
	7354	¾	21	44	42	14
	7355	1	29	56	47	21
	7356	1¼	36	70	58	21
	7357	1½	42	75	69	21
	7358	2	48	87	83	24

UL Listed liquidtight

*CSA Certified dust-tight and watertight

**UL not applicable and not CSA Certified