



Actual

**Catalog Number:** C75M-TB  
**Product ID:** 7TAD013210R0014  
**UPC Number:** 78621096193  
**Status:** A

Series 35 Thru-Feed, 3/4 Inch Conduit Body, Body Material Malleable Iron, Finish Zinc Plating with an Aluminum, Acrylic Coating for Use with Rigid/IMC Conduit

- Features tapered, threaded NPT hubs.
- Covers available in iron or stamped steel, both zinc-plated and supplied with stainless steel captive screws.
- Suitable for use in concrete.
- Serve as pulling outlets during conductor installation
- Provide easy access for splices in branch conductors
- Make 90 degree bends in conduit runs
- Act as mounting outlets for wiring devices and lighting fixtures
- Provide access to conductors for maintenance and future system changes

## North American Specifications (UNSPSC)

|                  |                                                                                                                                                                                        |
|------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| UNSPSC           | 39131708 Electrical conduit fitting body                                                                                                                                               |
| IGCC             | 5563 Electrical conduit fitting body                                                                                                                                                   |
| Brand Name       | T&B                                                                                                                                                                                    |
| Type             | Series 35 Conduit Body                                                                                                                                                                 |
| Special Features | Zinc-Plated Iron Construction with Aluminum Acrylic Coating Provides Durability, Impact Resistance and Corrosion Resistance.                                                           |
| Application      | Conduit Bodies are Installed In Conduit Systems to Connect Sections, Act As Pull Outlets When Conductors are Being Installed and Provide Easy Access for Splices In Branch Conductors. |
| Standard         | UL E2969                                                                                                                                                                               |
| Hub Size         | 3/4 Inch                                                                                                                                                                               |
| Material         | Malleable Iron                                                                                                                                                                         |
| Finish           | Zinc Plating with Aluminum Acrylic Coating                                                                                                                                             |

## Packaging

|                           |                |
|---------------------------|----------------|
| Inner Dimensions (inches) | xx             |
| Outer Quantity            | 10             |
| Outer Dimensions (inches) | 9.8x6.4x3.5    |
| Weight Uom                | 1.01 lbs. Each |

## Documents / Support Tools

|                                |            |
|--------------------------------|------------|
| Technical Drawing / Data Sheet | WSD-000253 |
|--------------------------------|------------|

**For further technical assistance, please contact us...**

ABB Installation Products - USA  
 860 Ridge Lake Blvd.  
 Memphis, TN 38120  
[www.tnb.com](http://www.tnb.com)

ABB Installation Products Technical Support  
 MS 3B-50  
 860 Ridge Lake Blvd.  
 Memphis, TN 38120

Hours: 7AM - 6PM CDT  
 Monday-Friday  
 Phone: (888) 862-3289  
 Fax: (901) 252-1321  
 Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)