

PHILIPS ADVANCE				e-Vision Electronic Ballast for Metal Halide Lamps			Catalog Number: IMH-39-G For 39W Metal Halide Lamps ANSI C130/M130 120-277V 50/60Hz Electronic Status: RELEASED			
DIMENSIONS AND DATA										
Lamp		Input Volts	Catalog Number*	Line Current (Amps)	Input Power (Watts)	Min Power Factor	Wiring Diag	Fig.	Weight (lb)	Max. Distance to Lamp (ft)
Number	Watts									
39W Watt Lamp, ANSI Code C130/M130 Minimum Starting Temp -20°C/-4°F										
1	39	120 277	IMH-39-G-XXX	0.37 0.17	44 43	0.9	3	G	0.9	3
Case Width Case Length Overall Length Height Mounting Width Mounting Length 2.0" [50.8] 8-32 x 1/4" Mounting Studs							Ballast (Red) (Blue) (White) (Black) (Green) Lamp Com 120V - 277V Ballast Case must be Grounded Wiring Diagram 3			
Case Figure	Overall Length	Case Length	Case Width	Height	Mountin Length	Mounting Width				
G	97mm [3.8"]	90mm [3.5"]	77mm [3.0"]	30mm [1.2"]	87mm [3.4"]	67mm [2.6"]				
12mm. Tcase max = 90 deg. C 45mm. Side Lead Version Angled Corner (Reference) Bottom Lead & Stud Version 12mm. Case Temperature Measurement Location							UL SP RoHS COMPLIANT 2011/65/EC			
INSTALLATION & APPLICATION NOTES:										
1. Maximum allowable case temperature is 90°C. See figure above for measurement location							*Ordering Information			
2. Ignition pulse is 4 kV max							Order Suffix	Description		
3. All leads are 9 inches long							-LF	Ballast with side exit leads and mounting feet		
4. Ballast output will shutdown after 20 minutes if lamp fails to ignite							-BLS	Ballast with bottom exit leads and mounting studs		
5. Power must be cycled off – then on, after replacing lamp										
6. Connect the red lead to the center terminals of the lamp when using screw base lamps										
Data is based on tests performed by Philips Advance in a controlled environment and is representative of relative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice. All specifications are nominal unless otherwise noted.										

Philips Lighting Electronics N.A.

10275 West Higgins Road • Rosemont, IL 60018 • www.philips.com/advance

Tel: 800-322-2086 • Fax: 800-423-1882 • Customer Support: 800-372-3331 • OEM Support: 866-915-5886