



Dependable Power for Any Application

hubbell-acmeelectric.com

www.hubbell.com

380/400/415 - 110/220
380/400/415 Primary Volts - 110/220 Secondary Volts - 1Ø - CE Marked
Industrial Control Transformer - Encapsulated

1067



Catalog #: CE040750

PRODUCT FEATURES

UL and cUL listed, CE Marked
Constructed out of electrical lamination with precision wound coils
Fully encapsulated core and coil
Available Fuse Kits and Accessories
Covered under Acme's 10 year limited warranty

BENEFITS

Molded terminal blocks with isolation barriers
Dual labeling for easy product identification
Heavy gauge steel mounting feet
Fast wire connection terminal

UL STANDARD

UL 506

CSA STANDARD

C22.2 No 66

WARRANTY

Acme Electric Warranty Card
www.hubbell-acmeElectric.com/Images/news/Acme_Warranty.pdf

GENERAL PRODUCT INFORMATION

VA:	750
Primary Voltage:	380/400/415
Secondary Voltage:	110/220
Frequency:	50/60 Hz
Max Temperature Rise:	55°C
UL Insulation Class:	105°C

PRODUCT MEASUREMENTS

Height (In./cm):	4.69 (11.9)
Width (In./cm):	5.25 (13.3)
Depth (In./cm):	6.81 (75.3)

CONFIGURATION

Mounting Type:	Floor
Wiring Diagram:	CE04

PACKAGING

Ship Weight (Lbs/Kg):	26.0 (11.8)
-----------------------	-------------

COMPLIANCES

UL Standard:	UL 506
UL Listed:	File E79947
CSA Standard:	C22.2 No 66
CSA Listed:	LR7357-16
CE:	CE Marked
Warranty:	Acme Electric Warranty Card
www.hubbell-acmeElectric.com/Images/news/Acme_Warranty.pdf	