



Allied Moulded switch and outlet boxes are molded of impact-resistant, high-strength fiberglass reinforced thermoset polyester material. Our fiberglassBOX™ “Premier Series” line of products was created for the

electrical contractor looking for nonmetallic outlet boxes with “hard box” characteristics. Allied Moulded’s fiberglassBOX line offers the following advantages:

- Non-corrosive
- Non-conductive, no ground required
- Non-distorting in high heat
- Will not melt
- Shatter resistant in cold temperatures
- Lightweight
- Heat insulator

2-Hour Wall and Ceiling Fire Classification

All Allied Moulded fiberglass boxes, including our 5305 five gang box, are classified by Underwriters Laboratories (UL®) for

use in 2-hour rated walls or ceilings.

During an actual fire test set up in a UL laboratory, Allied Moulded boxes passed all of the test criteria outlined in UL Standard 263 for both walls and ceilings.


Backed by even more UL® testing, the horizontal box separation requirement outlined in the Uniform Building Code™ can be reduced to as little as three inches without using any additional fire resistive protection. Allied Moulded fiberglass boxes, up to and including two three-gangs, can be mounted in the same stud cavity of fire rated walls **with absolutely no additional fire resistant protection needed.** In fact, only Allied Moulded has documentation covering all 52 U300 Series wall configurations, eliminating the need for additional putty pads, mineral wool insulation or alternate construction saving the contractor both time and money. See pages 4 and 5 for more information.

Look for our classification CEYY “Outlet Boxes and Fittings Classified for Fire Resistance” on our website at www.alliedmoulded.com or in the UL® online certification directory at www.ul.com. Additional documentation from these testing processes is available for examination upon request.

Labor Saving Features

With innovative products designed for the electrical contractor, Allied Moulded offers the largest, most complete line of box sizes and attachment brackets in the industry for a wide variety of applications. A few of the most popular attachments are:

- The “S” snap bracket or a “W” wing bracket for secure, old work box installation
- “BH” and 16” adjustable bar hangers for maximum support of ceiling boxes used for fixture support
- “Z” brackets with metal spurs to fasten wall boxes to wood or steel studs
- The “B” adjustable stabilizing bar, available on 3, 4 or 5 gang boxes, for more secure mounting used in conjunction with nails or “Z” brackets



- Offset gauge marks on box give positive stop for the proper wall thickness
- Bright common nails or pierce-point screws fit securely in specially designed supports and are angled for easy installation
- Strip-resistant, tapered and machine tapped device holes allow device screw to be started by hand and speed installation time with adjustable torque screwdrivers
- Cubic inch capacity clearly marked and easy for contractor and inspector to locate and identify
- Proudly UL® listed
- Knockouts on fiberglass boxes are complete, reducing drafts and are easily removed with wire for no-tool installation
- Leveling ribs position face of box parallel to wall surface
- “Z” brackets are designed to securely hold box to wood or steel studs; brackets also provide proper ¼” or ½” offset
- 2-Hour Fire Rated clearly marked for easy inspector identification
- Nonmetallic Speed “K” Klamps™ dependably secure wire in box (if a knockout is inadvertently opened and not used, the Speed “K” Klamp is considered sufficient closure of the opening per UL®)



Learn more about
our fiberglassBOX™
series online



LVP-1



LVP-1 Installed

Low Voltage Partition	Catalog Number	Component Description	UPC# 85339	Std. Pkg. Qty.	Std. Wt. (lb.)
	LVP-1	Low voltage divider plate for use with 2302, 3303, 4304, 5305 Series and 9314 only. See 2008 NEC 800.133(A)(1)(c).	80000	50*	3


* Consists of five (5) packages of ten (10) pieces each.



9312-EK



9312-EWC2




9312-EWC4



9312-EWK



9329-EWK



2TP

Ears	Cu. In. Volume	Catalog Number	Component Description	Exterior Dimensions			UPC# 85339	Std. Pkg. Qty.	Std. Wt. (lb.)
				D	W	H			
	28.0	9312-E	 Ears, Speed Klamps™- bulk packed	2-3/4	4-1/8	3-1/4	10064	50	23
	28.0	9312-EK	 Ears, Speed Klamps™- factory installed	2-3/4	4-1/8	3-1/4	29112	50	24

Ears & Wing Brackets	Cu. In. Volume	Catalog Number	Component Description	Exterior Dimensions			UPC# 85339	Std. Pkg. Qty.	Std. Wt. (lb.)
				D	W	H			
	28.0	9312-EW	 Ears, wing brackets, Speed Klamps™- bulk packed	2-3/4	4-1/8	3-1/4	29100	50	25
	28.0	9312-EWC2	 Ears, wing brackets, 2 wire clamps - factory installed	2-3/4	4-1/8	3-1/4	29110	50	26
	28.0	9312-EWC4	 Ears, wing brackets, 4 wire clamps - factory installed	2-3/4	4-1/8	3-1/4	29120	50	28
	28.0	9312-EWK	 Ears, wing brackets, Speed Klamps™- factory installed	2-3/4	4-1/8	3-1/4	29111	50	25
	32.5	9329-EW	 Ears, wing brackets, Speed Klamps™- bulk packed	3-1/4	4-1/8	3-1/4	10801	50	27
	32.5	9329-EWK	 Ears, wing brackets, Speed Klamps™- factory installed	3-1/4	4-1/8	3-1/4	10802	50	27

Template	Catalog Number	Component Description	UPC# 85339	Std. Pkg. Qty.	Std. Wt. (lb.)
	2TP	 Metal template for two gang old work box: 9312-E series, 9329-E series	88016	1	2

All dimensions are in inches unless otherwise noted.
See page 7 for Attachment Coding suffix descriptions.

 Old Work/Manufactured Housing Boxes

 Flush-Device Box
UL File No. E30594