

Threaded Rigid Conduit and IMC Enlargers and Nipples

Applications



- Male enlargers:
 - Used to adapt an outlet hole to the next larger size of conduit.
- Offset nipples:
 - Provides box to box connection of knockouts
 - Allows misaligned knockout connection by rolling the offset nipple until aligned with each knockout
- Bushed nipples:
 - Used through knockout to connect box to conduit coupling
 - Used with a locknut to connect two boxes side by side or back to back
 - Used with a locknut to connect fixture housings and continuous runs

Material/Finish

- Male enlargers: turned steel
- Offset nipples: malleable iron/zinc plated
- Bushed nipples: malleable iron/zinc plated

Certifications and Compliances

- UL Standard: 514B
- UL Listed: E11853, E14814
- CSA Standard: C22.2 No. 18.3
- CSA Certified: 009795, 065178
- NEMA: FB-1

	Trade Size (Inches)	Dimensions in Millimeters (Inches)			Weight per 100 kg (lb)	Catalog Number	
		A	B	C			
Male Enlargers ① — Turned Steel ①							
	1/2	14.2 (0.56)	19.8 (0.78)	35.1 (1.38)	7.26 (16.00)	ME50-75 ②	
	3/4	12.7 (0.50)	23.9 (0.94)	44.5 (1.75)	1.80 (26.00)	ME75-100 ②	
	1	14.2 (0.56)	26.9 (1.06)	57.2 (2.25)	21.32 (47.00)	ME100-125 ②	
Offset Nipples — Malleable Iron/Zinc Plated							
	1/2	41.4 (1.63)	11.2 (0.44)	19.1 (0.75)	10.43 (23.00)	OFN-50	
	3/4	41.4 (1.63)	11.2 (0.44)	19.1 (0.75)	14.06 (31.00)	OFN-75	
	1	41.4 (1.63)	12.7 (0.50)	19.1 (0.75)	19.96 (44.00)	OFN-100	
	1-1/4	41.4 (1.63)	14.2 (0.56)	19.1 (0.75)	27.22 (60.00)	OFN-125	
	1-1/2	41.4 (1.63)	16.0 (0.63)	19.1 (0.75)	37.19 (82.00)	OFN-150	
	2	41.4 (1.63)	19.1 (0.75)	19.1 (0.75)	50.80 (112.00)	OFN-200	

① Not CSA Certified.

② Not UL Listed.