

Appleton® EYS 25% * Fill Vertical Sealing Fittings for Close Turning Radius

Explosionproof, Dust-Ignitionproof, Raintight

UNILETS® for Use with Threaded Rigid Metal Conduit and IMC.


NEC/CEC:

Class I, Division 1 and 2, Groups A◇, B, C, D

Class II, Division 1 and 2, Groups E, F, G

Class III

		Trade Size (Inches)	Millimeters (Inches)			Kwiko® A Cement Required Grams (Ounces)	Catalog Number Grayloy™–Iron
		A (Length)	B (Width)	Turning Radius ①			
EYS Vertical Sealing Fittings (25% fill)							
		Female					
	1/2	83.3 (3.28)	31.7 (1.25)	41.4 (1.63)		28.4 (1.00)	EYS-1 ◊
	3/4	93.7 (3.69)	38.1 (1.50)	48.5 (1.91)		56.8 (2.00)	EYS-2 ◊
	1	109.4 (4.31)	44.4 (1.75)	60.4 (2.38)		85.1 (3.00)	EYS-3 ◊
		Male/Female (Removable Male Nipple)					
	1/2	83.3 (3.28)	31.7 (1.25)	41.4 (1.63)		28.4 (1.00)	EYS-16 ◊
	3/4	93.7 (3.69)	38.1 (1.50)	48.5 (1.91)		56.8 (2.00)	EYS-26 ◊
	1	109.4 (4.31)	44.4 (1.75)	60.4 (2.38)		85.1 (3.00)	EYS-36 ◊
Female	Male						



* Per NEC 501.15(C)(6), seals in Class I, Division 1 and 2 must be limited to conductor fill of 25% of cross sectional area of a rigid metal conduit of the same trade size unless approved for higher percentage fill. See 40% fill sealing fittings.

① Turning radius with cover or plug removed.

◇ Indicates items in the shaded area which are UL Listed for Class I, Groups A, B, C, D; Class II, Groups E, F, G; and Class III.