

# Powertite™ Series Pin and Sleeve Plugs, Connectors and Receptacles

NEC/CEC:  
Listed for Ordinary (Unclassified) Locations  
NEMA 3, 3R, 4, 4X

## Applications

- Designed to supply power to portable or fixed electrical equipment such as motor generator units, welders, pumps, compressors, cellular relay stations, and similar apparatus.
- Ideal for use on shipping docks, ports, and other "ship to shore" applications.
- Suitable for use in locations where a weatherproof enclosure is required.
- Rough usage construction.

## Features

- Available in 30, 60, 100, 150, 200, and 400 Amp units.
- Available in two grounding styles: Style 1 (shell only) and Style 2 (shell and extra pole).
- Neoprene bushing compressed by cable collar prevents entrance of water. Bushing is highly resistant to hydrocarbon deterioration and is self-extinguishing.
- Locking screw and slot prevents plug cable collar from "backing off."
- Contacts exert constant pressure along entire contact surface and provide electrical continuity.
- Suitable for use from -40 °C to 107 °C (-40 °F to 225 °F).
- Insulating blocks provide greatest dielectric and mechanical strength and lowest arc tracking.
- Positive polarization: only plugs and receptacles of same style, number of poles and ampere rating can be used together.
- Circuit breaking: in 30, 60, 100, 150 and 200 Amp units, any arcing created as line and load terminals disengage is safely confined deep within terminal cavities. Plugs may be withdrawn in an emergency under full rated loads without separate disconnect switches (400 Amp plug is for disconnecting use only; not for current rupturing).
- 30, 60, 100, and 150 Amp Powertite™ plugs also suitable for classified locations when used with Appleton EBR, EBRH, JBR, MD2SR, or DBR explosionproof interlocking receptacles.
- Controlled length contacts ensure that ground makes first and breaks last for added safety.

## Standard Materials

- Plug, receptacle, connector and mounting box housings: copperfree (4/10 of 1% max.) aluminum
- Insulating blocks: glass filled polyester

## Standard Finishes

- Aluminum plug, receptacle, connector and mounting box housings: epoxy powder coat
- Insulating blocks and contacts: natural finish

## Options

- See Illustrated Options

## NEC/CEC Certifications and Compliances

- UL Standard: UL 1682, UL 1686 ①, UL 50E
- UL Listed: E145916, E145917
- CSA Standard: C22.2 No. 182.1
- CSA Certified: 065179
- NEMA 4X (30, 60, 100, 150, and 200 Amp)
- NEMA Configuration: FB11

## Related Products

- For classified location plugs and receptacles, see *Plugs and Receptacles: Hazardous Location*.

① UL 1686 does not apply to 150, 200 or 500 Amp units.

Classified by UL and Certified by CSA for use in specific combinations with Crouse-Hinds Arkrite. Arkrite is a registered trademark of Cooper Crouse-Hinds.




30 and 60 Amp



100 and 150 Amp



200 Amp



400 Amp


PLUGS AND RECEPTACLES: NEC/CEC ORDINARY LOCATION

Appleton®

# Powertite™ Series Pin and Sleeve Plugs, Connectors and Receptacles

NEC/CEC:  
Listed for Ordinary (Unclassified) Locations  
NEMA 3, 3R, 4, 4X

## Illustrated Features



PLUGS AND RECEPTACLES: NEC/CEC ORDINARY LOCATION


Appleton®

# Powertite™ Series Pin and Sleeve Plugs, Connectors and Receptacles


NEC/CEC:  
Listed for Ordinary (Unclassified) Locations  
NEMA 3, 3R, 4, 4X

## Illustrated Features

### Grounding Styles




**Style 1  
(Shell Only)**




**Plug**—Equipment grounding conductor is wired directly to solderless lug which is connected to the plug housing with a pressure connector. All terminals are "current carrying."

**Receptacle**—Two detent spring clips engage the grounded plug housing on plug insertion—grounded plug shell makes contact with receptacle ground spring before line and load poles are engaged. Grounding path is maintained until after current-carrying contacts disengage. All terminals are "current carrying."



**Style 2  
(Shell and Extra Pole)**




**Plug**—Equipment grounding conductor is not only connected to the solderless lug in the plug housing, but also to an extra grounding pole. Grounding pole has copper alloy grounding jumper strap that connects to plug housing.

**Receptacle**—Two detent spring clips engage grounded plug housing on plug insertion. Jumper from extra grounding pole is electrically connected to a screw on receptacle housing. Longer grounding pole "makes first and breaks last."

### Pin and Sleeve Design ①



**30, 60, and 100 Amp Pressure Wire Terminals.  
Solid Brass Contacts with Beryllium Copper Springs.**




**150 Amp Pressure Wire Terminals.  
Solid Copper Contacts with Beryllium Copper Springs.**



**200 Amp Pressure Wire Terminals. Solid Copper Split-Type Contact.**



**400 Amp 0.84" Solder Well Wire Terminals. Solid Copper Contacts with Four Spring-Loaded Borosilicate Bearings.**



**400 Amp 1.25" Solder Wire Well Terminals. Solid Copper Contacts with Four Spring-Loaded Borosilicate Bearings.**

① Pins and sleeves are not sold separately. Must be purchased as entire interior replacement. Available on the Replacement Interiors pages.

# Powertite™ Series Pin and Sleeve Plugs, Connectors and Receptacles

## NEC/CEC:

Listed for Ordinary (Unclassified) Locations  
NEMA 3, 3R, 4, 4X

## Illustrated Features

### Spring Door and Screw Cap

30, 60, 100, and 150 Amp spring door and screw cap receptacles are threaded to accept clamping ring ACP plug. The ring threads onto the receptacle to form a raintight assembly with plug in use-and also to prevent plug fallout. When the plug is withdrawn, the gasketed spring door cover closes tightly against receptacle opening automatically, providing weatherproof protection. Spring door has stainless steel spring and shaft.



### Spring Door Cover

30, 60, 100, and 150 Amp units may be located at any position in a 360° circle by adjusting a setscrew. Set screw also allows complete removal of cover. Spring door available on 200 Amp units.

NOTE: Spring Door cover in open positions for illustration only.



### ACP Plugs

Supplied with bushings to accommodate a wide variety of cable diameters. 30 Amp plug clamp used in first position with smallest inside diameter bushing provides positive grip on cables as small as 0.390 inches, such as those that are used in oil rig installations.



### Reversible Cable Clamps


Permits wide cable range (just loosen screws and flip over). Each position accommodates one of two bushings. Convenient in installations having different cable sizes.



## Illustrated Options


### Standard Service

Energized receptacle has recessed male contacts to reduce danger of accidental touching. Plug has female contacts that are energized only upon insertion in receptacle.



### Reverse Service (Generator Application)

Useful where a "hot" plug feeds a dead receptacle. Reverse service is often used for generator applications where the receptacle houses a dead plug interior. Plug houses an energized receptacle interior, which has recessed male contacts to reduce danger of accidental touching. 30, 60, 100, 150, and 200 Amp units can be easily converted to reverse service in the field when matching plug and receptacle are ordered. 400 Amp unit is only available as a factory assembled item at extra cost. Add suffix **-RS** to receptacle or connector.



### Special Polarization

Special polarization is available on 30, 60, 100, 200, and 400 Amp units. Prevents plug insertion in a receptacle or connector wired for a different voltage. In installations where there are different line voltages, the special polarization option is desirable. This allows only plugs and receptacles wired for the same line voltage to be mated together. The receptacle or connector interior is positioned 22-1/2°, relative to the polarization rivet, to the right (as specified) of standard, and plug is polarized to correspond. Add suffix **-P4** to the standard or reverse service plug, receptacle or connector.

# Powertite™ Series Pin and Sleeve Plugs, Connectors and Receptacles

NEC/CEC:  
Listed for Ordinary (Unclassified) Locations  
NEMA 3, 3R, 4, 4X

## Features at a Glance

| Amp | Receptacle Types |                          |                   |                       | Brass with Beryllium Copper Springs | Copper with Borosilicate Bearings | Contacts Split-type Copper Contacts | Brass Ground Contacts | Reverse Service |              |
|-----|------------------|--------------------------|-------------------|-----------------------|-------------------------------------|-----------------------------------|-------------------------------------|-----------------------|-----------------|--------------|
|     | Grounding Styles | Weatherproof Spring Door | NEMA 4X Screw Cap | Raintight Clamp Cover |                                     |                                   |                                     |                       | In Field        | Factory Only |
| 30  | 1 and 2          | X                        | X                 |                       | X                                   |                                   |                                     | Style 2               | X               |              |
| 60  | 1 and 2          | X                        | X                 |                       | X                                   |                                   |                                     | Style 2               | X               |              |
| 100 | 1 and 2          | X                        | X                 |                       | X                                   |                                   |                                     | Style 2               | X               |              |
| 150 | 2                | X                        | X                 |                       | X ②                                 |                                   |                                     | Style 2               | X               |              |
| 200 | 1 and 2          | X ▼                      |                   | X ▼                   |                                     |                                   | X                                   | Style 2               | X ①             |              |
| 400 | 1 and 2          |                          |                   |                       |                                     | X                                 |                                     | Style 2               |                 | X            |

## Application Chart

| Grounding Style                | Wire/Pole | Single Phase |                 | Grounding Style                | Wire/Pole | Three Phase  |                 |
|--------------------------------|-----------|--------------|-----------------|--------------------------------|-----------|--------------|-----------------|
|                                |           | With Neutral | Without Neutral |                                |           | With Neutral | Without Neutral |
| Style 1 (Shell Only)           | 2W, 2P    | L1+N+G       | L1+L2+G         | Style 1 (Shell Only)           | 2W, 2P    |              |                 |
|                                | 3W, 3P    | L1+L2+N+G    |                 |                                | 3W, 3P    |              | L1+L2+L3+G      |
|                                | 4W, 4P    |              |                 |                                | 4W, 4P    | L1+L2+L3+N+G |                 |
| Style 2 (Shell and Extra Pole) | 2W, 3P    | L1+N+G       | L1+L2+G         | Style 2 (Shell and Extra Pole) | 2W, 3P    |              |                 |
|                                | 3W, 4P    | L1+L2+N+G    |                 |                                | 3W, 4P    |              | L1+L2+L3+G      |

**Powertite™ Horsepower Ratings** Plug may be withdrawn in an emergency if within these maximum HP ratings. Not for normal starting/stopping.

| Motor Horsepower                              |      |                              |         |         |         |
|-----------------------------------------------|------|------------------------------|---------|---------|---------|
| Phase Motor                                   | Amps | 115 Vac                      | 230 Vac | 480 Vac | 600 Vac |
| For Emergency Disconnect Only                 |      |                              |         |         |         |
| 3-Phase<br>3W, 3P;<br>3W, 4P;<br>or<br>4W, 4P | 30   | 3                            | 7-1/2   | 15      | 20      |
|                                               | 60   | 7-1/2                        | 15      | 30      | 30      |
|                                               | 100  | 10                           | 20      | 40      | 40      |
|                                               | 150  | Do Not Disconnect Under Load |         |         |         |
|                                               | 200  | 20                           | 40      | 50      | 50      |

| Motor Horsepower                  |      |         |         |         |         |
|-----------------------------------|------|---------|---------|---------|---------|
| Phase Motor                       | Amps | 115 Vac | 230 Vac | 480 Vac | 600 Vac |
| 1-Phase<br>2W, 2P<br>or<br>2W, 3P | 30   | 2       | 3       | 10      | 10      |
|                                   | 60   | 3       | 10      | 20      | 20      |
|                                   | 100  | 7-1/2   | 15      | 30      | 30      |
|                                   | 200  | 15      | 30      | 40      | 40      |

## Range of Wire Sizes Accommodated in Powertite™ Plug and Receptacle Terminals

60 °C (140 °F) minimum wire ratings.

| 30, 60, 100, and 150 Amp |                           |                     |             | 200 Amp                   |                |                | 400 Amp                     |                |                |
|--------------------------|---------------------------|---------------------|-------------|---------------------------|----------------|----------------|-----------------------------|----------------|----------------|
| Amps                     | Wire Recess Dia. (Inches) | Wire Range Building | Extra Flex. | Wire Recess Dia. (Inches) | Conductor Size | Type Conductor | Solder Recess Dia. (Inches) | Conductor Size | Type Conductor |
| 30                       | .281                      | #10 – #6            | #10 – #8    | 0.687                     | 250            | General Wire   | 0.84                        | 500 MCM        | General Wire   |
| 60                       | .312                      | #6 – #2             | #6 – #4     |                           | 4/0            | General Wire   |                             | 400 MCM        | Flex. Cable    |
| 100                      | .391                      | #4 – #1             | #4 – #2     |                           | 4/0            | Flex. Cable    |                             | 400 MCM        | Extra Flex.    |
| 150                      | .525                      | #2 – 2/0            | #2 – 2/0    |                           | 3/0            | Flex. Cable    | 1.25                        | 1000 MCM       | General wire   |
|                          |                           |                     |             |                           | 3/0            | Extra Flex.    |                             | 900 MCM        | General Wire   |
|                          |                           |                     |             |                           | 2/0            | Flex. Cable    |                             | 800 MCM        | Extra Flex.    |

▼ NEMA 4X.

① For receptacle only.

② Copper with beryllium copper springs.

# Powerlite™ 100 and 150 Amp Pin and Sleeve Plugs and Receptacles

600 Vac, 250 Vdc, 50-400 Hz

Pressure Wire Terminals – 100 Amp: Wire Recess Diameter: .391". Wire Size Range: #4—#1 Building; #4—#2 Extra Flex.

150 Amp: Wire Recess Diameter: .525". Wire Size Range: #2—2/0 Building; #2—#2/0 Extra Flex.

NEC/CEC:

Listed for Ordinary (Unclassified) Locations

NEMA 3, 3R, 4, 4X



| Grounding Style                        | Wire/Pole | Receptacle with AJA Mounting Box ① | Hub Size (Inches) | Receptacle Only ③ | Clamping Ring Plug ② | Plug Cable Dia. (Inches) |
|----------------------------------------|-----------|------------------------------------|-------------------|-------------------|----------------------|--------------------------|
| 100 Amp Style 1 (Shell Only)           | 2W, 2P    | ADJA1022-125                       | 1-1/4             | ADR1022           | ACP1022CD            | .875 to 1.906            |
|                                        |           | ADJA1022-150                       | 1-1/2             |                   |                      |                          |
|                                        | 3W, 3P    | ADJA1033-125                       | 1-1/4             | ADR1033           | ACP1033CD            | .875 to 1.906            |
|                                        |           | ADJA1033-150                       | 1-1/2             |                   |                      |                          |
|                                        | 4W, 4P    | ADJA1044-150                       | 1-1/2             | ADR1044           | ACP1044CD            | .875 to 1.906            |
|                                        |           | ADJA1044-200                       | 2                 |                   |                      |                          |
| 100 Amp Style 2 (Shell and Extra Pole) | 2W, 3P    | ADJA1023-125                       | 1-1/4             | ADR1023           | ACP1023CD            | .875 to 1.906            |
|                                        |           | ADJA1023-150                       | 1-1/2             |                   |                      |                          |
|                                        | 3W, 4P    | ADJA1034-150                       | 1-1/2             | ADR1034           | ACP1034CD            | .875 to 1.906            |
|                                        |           | ADJA1034-200                       | 2                 |                   |                      |                          |
| 150 Amp Style 2 (Shell and Extra Pole) | 3W, 4P    | ADJA15034-150                      | 1-1/2             | ADR15034          | ACP15034CD           | .875 to 1.906            |
|                                        |           | ADJA15034-200                      | 2                 |                   | ACP15034DE           | 1.250 to 2.187           |

Receptacles are provided with spring door and screw cover.

For Reverse Service, add suffix **-RS** to Catalog Number.

For Special Polarization for 100 Amp units, add suffix **-P4** to Catalog Number. (Not available for 150 Amp units.)

## Horsepower Ratings for Emergency Disconnect Under Load

Not for normal starting and stopping, but plug may be withdrawn in an emergency if within these maximum HP ratings.

| Amp | Motor Phase | Wire/Pole                 | Motor Horsepower             |         |         |         |
|-----|-------------|---------------------------|------------------------------|---------|---------|---------|
|     |             |                           | 120 Vac                      | 240 Vac | 480 Vac | 600 Vac |
| 100 | 1-Phase     | 2W, 2P or 2W, 3P          | 7-1/2HP                      | 15HP    | 30HP    | 30HP    |
|     | 3-Phase     | 3W, 3P; 3W, 4P; or 4W, 4P | 10HP                         | 20HP    | 40HP    | 40HP    |
| 150 | 3-Phase     | 3W, 4P                    | Do Not Disconnect Under Load |         |         |         |

① For additional mounting boxes, see Aluminum Mounting Boxes.

② Plug and receptacle combination is NEMA 4X rated when clamping ring is fully tightened on receptacle.

③ Receptacle is NEMA 4X rated when screw cover is fully engaged when the receptacle is not in use.