

# ELBY Capped Elbows

## Explosionproof, Dust-Ignitionproof

UNILETS™ for use with Threaded Metal Conduit.

NEC/CEC — Aluminum and Malleable Iron:  
Class I, Division 1 and 2, Groups B ♦, C, D  
Class II, Division 1 and 2, Groups E, F, G  
Class III

NEC/CEC — Malleable Iron Only:  
Class I, Zone 1 and 2, Groups IIA, IIB +H<sub>2</sub>

### Applications

- Serves as pulling fitting.
- Makes 90° bend in conduit runs.

### Features

- Screw-on Cover for ease of installation and removal.
- Cover opens on an angle permitting conductors to be pulled straight through either hub.
- Can make 90° turns in conduit where a compact turn is desired.
- Female tapered threaded hubs (NPT) for rigid conduit and IMC.



### Standard Materials

- Malleable iron or aluminum

### Standard Finishes

- Aluminum: epoxy powder coat
- Malleable iron: triplecoat— (1) zinc electroplate, (2) chromate, and (3) epoxy powder coat

### NEC/CEC Certifications and Compliances

- UL Standard: 886 (1203)
- UL Listed: E10444
- CSA Standard: C22.2 No. 30
- CSA Certified: 065181

| Type and Size (Inches) | Catalog Number |           |
|------------------------|----------------|-----------|
|                        | Malleable Iron | Aluminum  |
| 1/2                    | ELBY-50 ♦      | ELBY-50A  |
| 3/4                    | ELBY-75 ♦      | ELBY-75A  |
| 1                      | ELBY-100 ♦     | ELBY-100A |
| 1-1/4                  | ELBY-125 ♦     | ELBY-125A |

♦ Suitable for Class 1, Group B in addition to Class I, Groups C, D; Class II, Groups E, F, G and Class III.