

STAINLESS STEEL FLEXIBLE CONDUIT (Type 316SS)


Coated Flex Conduit 25' Length			NEMA4X Suitable for damp locations			
Trade Size	Metric Size	Diameters		Bend	Wt. 25 Coil (lbs)	Part Number
		OD	ID			
½"	16	0.840"	0.610"	4 ½"	5.50"	S60500CTFC
¾"	21	1.050"	0.790"	6"	7.00"	S60700CTFC
1"	27	1.315"	1.010"	10"	9.00"	S61000CTFC
1 ¼"	35	1.660"	1.330"	11"	11.00"	S61200CTFC
1 ½"	41	1.900"	1.520"	12"	12.00"	S61500CTFC
2"	53	2.370"	2.060"	14"	20.00"	S62000CTFC



Clear Coated Flex Conduit 25' Length			NEMA4X Suitable for damp locations			
Trade Size	Metric Size	Diameters		Bend	Wt. 25 Coil (lbs)	Part Number
		OD	ID			
½"	16	0.840"	0.610"	4 ½"	5.50"	S60500CTCC
¾"	21	1.050"	0.790"	6"	7.00"	S60700CTCC
1"	27	1.315"	1.010"	10"	9.00"	S61000CTCC
1 ¼"	35	1.660"	1.330"	11"	11.00"	S61200CTCC
1 ½"	41	1.900"	1.520"	12"	12.00"	S61500CTCC
2"	53	2.370"	2.060"	14"	20.00"	S62000CTCC




Bare Flex Conduit 25' Length						
Trade Size	Metric Size	Diameters		Bend	Wt. 25 Coil (lbs)	Part Number
		OD	ID			
½"	16	0.744"	0.610"	4"	4.50"	S60500CTFX
¾"	21	0.960"	0.790"	4 ½"	5.50"	S60700CTFX
1"	27	1.160"	1.010"	6"	7.00"	S61000CTFX
1 ¼"	35	1.500"	1.330"	7 ½"	8.50"	S61200CTFX
1 ½"	41	1.750"	1.520"	9"	10.00"	S61500CTFX
2"	53	2.125"	2.020"	10"	13.00"	S62000CTFX




STAINLESS STEEL FLEXIBLE CONNECTORS (Type 316SS)

Flex Connector Male 90 Elbow			NEMA4X Suitable for damp locations			
Trade Size	Metric Size	Wt. (lbs)	A	B	C	Part Number
½"	16	0.27	1.950"	1.250"	2.150"	S60500FC90
¾"	21	0.50	2.250"	1.540"	2.630"	S60700FC90
1"	27	0.72	2.800"	1.860"	3.000"	S61000FC90
1 ¼"	35	0.95	3.150"	2.250"	3.150"	S61200FC90
1 ½"	41	1.55	3.750"	2.580"	3.750"	S61500FC90
2"	53	2.35	4.450"	3.050"	4.750"	S62000FC90



Flex Connector Male Straight			NEMA4X Suitable for damp locations		
Trade Size	Metric Size	Wt. (lbs)	A	B	Part Number
½"	16	0.17	1.950"	1.250"	S60500FCS0
¾"	21	0.24	2.250"	1.540"	S60700FCS0
1"	27	0.33	2.800"	1.650"	S61000FCS0
1 ¼"	35	0.58	3.150"	2.250"	S61200FCS0
1 ½"	41	0.85	3.750"	2.650"	S61500FCS0
2"	53	1.19	4.450"	3.210"	S62000FCS0



• 45° Flex Connectors available in ½", ¾" and 1"