

| Models      | Base Connection                                                                                                     | Light Connection                                                                                                                                      | Brackets                                                                                            |                                                                                                     |                                                                                                  |
|-------------|---------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------|
| FLX18-1212  | <br>1/2-14 NPSM                    | <br>1/2-14 NPSM (Male)<br>Use with:<br>WL50-2<br>WL50-2PB            | <br>SMB22          | <br>SMBFLXMAG    | <br>LMB12RA   |
| FLX18-F12   | <br>3-Hole Flange                  | <br>1/2-14 NPSM (Male)<br>Use with:<br>WL50-2<br>WL50-2PB            | Direct Mount                                                                                        |                                                                                                     |                                                                                                  |
| FLX18-12M30 | <br>1/2-14 NPSM                   | <br>M30 x 1.5 (Female)<br>Use with:<br>WL50-2<br>WL50-2PB<br>WL50S   | <br>SMB22         | <br>SMBFLXMAG   | <br>LMBE12RA |
| FLX18-DM30  | <br>2 x 1/4-20W<br>1.375 spacing | <br>M30 x 1.5 (Female)<br>Use with:<br>WL50-2<br>WL50-2PB<br>WL50S | <br>SMBFLXCLAMPD | <br>SMBFLXMAGD |                                                                                                  |
| FLX18-FM30  | <br>3-Hole Flange                | <br>M30 x 1.5 (Female)<br>Use with:<br>WL50-2<br>WL50-2PB<br>WL50S | Direct Mount                                                                                        |                                                                                                     |                                                                                                  |

Elevated Mount System

| Features                                                                                                                                                                                                                                                                                   | Model                                     |                                          |                                           | Components                                                                          |                                                                                     |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------|------------------------------------------|-------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"><li>Streamlined black acetal or white UHMW stand-off pipe adapter/cover</li><li>Connects to 30 mm light base</li><li>Mounting hardware included</li></ul>                                                                                                | use with TL50 and CL50 models             | <b>SA-M30TE12</b><br>(black ABS)         | <b>SA-M30TE12C</b><br>(whiteTL50 ABS)     |  |  |
|                                                                                                                                                                                                                                                                                            | Use with TL70 Models                      | <b>SA-M30</b><br>(black ABS)             | <b>SA-M30C</b><br>(white ABS)             |                                                                                     |                                                                                     |
| <ul style="list-style-type: none"><li>Elevated-use stand-off pipe (½ in. NPSM/DN15)</li><li>Polished 304 stainless steel, black anodized aluminum, or clear anodized aluminum surface</li><li>½ in. NPT thread at both ends</li><li>Compatible with most industrial environments</li></ul> | <b>Polished 304 Stainless Steel</b>       | <b>Black Anodized Aluminum</b>           | <b>Clear Anodized Aluminum</b>            |  |                                                                                     |
|                                                                                                                                                                                                                                                                                            | <b>SOP-E12-150SS</b><br>150 mm (6") long  | <b>SOP-E12-150A</b><br>150 mm (6") long  | <b>SOP-E12-150AC</b><br>150 mm (6") long  |                                                                                     |                                                                                     |
|                                                                                                                                                                                                                                                                                            | <b>SOP-E12-300SS</b><br>300 mm (12") long | <b>SOP-E12-300A</b><br>300 mm (12") long | <b>SOP-E12-300AC</b><br>300 mm (12") long |                                                                                     |                                                                                     |
|                                                                                                                                                                                                                                                                                            | <b>SOP-E12-900SS</b><br>900 mm (36") long | <b>SOP-E12-900A</b><br>900 mm (36") long | <b>SOP-E12-900AC</b><br>900 mm (36") long |                                                                                     |                                                                                     |
| <ul style="list-style-type: none"><li>Streamlined black acetal or white UHMW mounting base adapter/cover</li><li>Connects between ½ in. NPSM/DN15 pipe and 30 mm (1-3/16 in) drilled hole</li><li>Mounting hardware included</li></ul>                                                     | <b>SA-E12M30</b><br>(black zinc and ABS)  |                                          |                                           |  |                                                                                     |
|                                                                                                                                                                                                                                                                                            | <b>SA-E12M30C</b><br>(white zinc and ABS) |                                          |                                           |                                                                                     |                                                                                     |

EZ-LIGHT® Controllers

| Description       | Function     | Model |                                                                                     |
|-------------------|--------------|-------|-------------------------------------------------------------------------------------|
| 5 toggle switches | ON-OFF-FLASH | LC80T |  |

|                           |              |       |                                                                                     |
|---------------------------|--------------|-------|-------------------------------------------------------------------------------------|
| 12 position rotary switch | ON-OFF-FLASH | LC80R |  |
|---------------------------|--------------|-------|-------------------------------------------------------------------------------------|

EZ-LIGHT® Sealed Right-Angle Brackets

| Description                                                                                                                                    | Model     |                                                                                       |                                                                                       |
|------------------------------------------------------------------------------------------------------------------------------------------------|-----------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| Bracket kit with base, ½-14 pipe adapter, set screw, fasteners, o-rings and gaskets. For use with stand-off pipe (listed and sold separately). | LMBE12RA  |  |  |
|                                                                                                                                                | LMBE12RAC |  |                                                                                       |

|                                                                                 |          |                                                                                       |                                                                                       |
|---------------------------------------------------------------------------------|----------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| Bracket kit with base, 30 mm adapter, set screw, fasteners, o-rings and gaskets | LMB30RA  |  |  |
|                                                                                 | LMB30RAC |  |                                                                                       |