

Elevated Mount System

Features	Model			Components	
- Streamlined black acetal or white UHMW stand-off pipe adapter/cover - Connects to 30 mm light base - Mounting hardware included	use with TL50 and CL50 models	SA-M30TE12 (black ABS)	SA-M30TE12C (whiteTL50 ABS)		
	Use with TL70 Models	SA-M30 (black ABS)	SA-M30C (white ABS)		
- Elevated-use stand-off pipe (½ in. NPSM/DN15) - Polished 304 stainless steel, black anodized aluminum, or clear anodized aluminum surface ½ in. NPT thread at both ends - Compatible with most industrial environments	Polished 304 Stainless Steel	Black Anodized Aluminum	Clear Anodized Aluminum		
	SOP-E12-150SS 150 mm (6") long	SOP-E12-150A 150 mm (6") long	SOP-E12-150AC 150 mm (6") long		
	SOP-E12-300SS 300 mm (12") long	SOP-E12-300A 300 mm (12") long	SOP-E12-300AC 300 mm (12") long		
	SOP-E12-900SS 900 mm (36") long	SOP-E12-900A 900 mm (36") long	SOP-E12-900AC 900 mm (36") long		
- Streamlined black acetal or white UHMW mounting base adapter/cover - Connects between ½ in. NPSM/DN15 pipe and 30 mm (1-3/16 in) drilled hole - Mounting hardware included					
	SA-E12M30 (black zinc and ABS)				
	SA-E12M30C (white zinc and ABS)				

EZ-LIGHT® Controllers

Description	Function	Model	
5 toggle switches	ON-OFF-FLASH	LC80T	

12 position rotary switch	ON-OFF-FLASH	LC80R	
---------------------------	--------------	-------	---

EZ-LIGHT® Sealed Right-Angle Brackets

Description	Model		
Bracket kit with base, ½-14 pipe adapter, set screw, fasteners, o-rings and gaskets. For use with stand-off pipe (listed and sold separately).	LMBE12RA		
	LMBE12RAC		

Bracket kit with base, 30 mm adapter, set screw, fasteners, o-rings and gaskets	LMB30RA		
	LMB30RAC		