

Machine Interface Connections



8-Pin

RD Cordsets

RDLS-815
4.6 m (15')
RDLS-825
8 m (26')
RDLS-860
15 m (60')

NOTE: 5-pin options available



8-Pin

M12/Euro-Style
Straight connector
models listed

QDE-815D
4.5 m (15')
QDE-825D
7.6 m (25')
QDE-850D
15.3 m (50')
QDE-875D
22.9 m (75')
QDE-8100D
30.5 m (100')



Euro-Style
Straight splitter

8-Pin

CSB-M1280M1280
CSB-M1281M1281
CSB-M1288M1281
CSB-M12815M1281
CSB-M12825M1281



Euro-Style
Double-ended
male/female

8-Pin*

DEE2R-81D
0.3 m (1')
DEE2R-83D
0.9 m (3')
DEE2R-88D
2.4 m (8')
DEE2R-815D
4.5 m (15')

DEE2R-825D
7.6 m (25')
DEE2R-850D
15.3 m (50')
DEE2R-875D
22.9 m (75')
DEE2R-8100D
30.5 m (100')

Cascading Connections



Double-ended
RD to RD

DELS-110E
0.05 m (0.2')
DELS-111E
0.3 m (1')
DELS-113E
1 m (3.3')
DELS-118E
2.5 m (8.2')

DELS-1115E
4.6 m (15')
DELS-1125E
8 m (26')
DELS-1150E
15.3 m (50')

Additional cordset information is available.
See page 758



EZLSA-MBK-11



EZLSA-MBK-12



EZLSA-MBK-16



EZLSA-MBK-20

Additional bracket information is available.
See page 729



EZLSA-K30LGR
Connects directly to **SLLCR...**
cascade receiver



K30LGRXPQ
requires 4-pin QD



K50LGRXPQ
requires 4-pin QD



TL50GRQ
requires 4-pin QD



RD to Euro-Style*
Connects indicators
to a cascade receiver

DELSEF-40D
0.5 m (0.02')
DELSEF-41D
0.3 m (1')
DELSEF-43D
1 m (3.3')
DELSEF-48D
2.5 m (8.2')
DELSEF-415D
4.6 m (15.1')

NOTE: For Remote Fixed Blanking use **DELSEF-81D**