

E-Stop Buttons

Illuminated Flush Mount



- Illumination allows for easy identification of which E-stop has been activated.
- Easy installation with no assembly or individual wiring required
- Remotely located E-Stop buttons can be positioned to be clearly identified, clearly visible and readily accessible
- Push-to-stop, twist-to-release or pull-to-release operation per IEC 60947-5-5
- Compliant with ANSI B11.19, ANSI NFPA79 and IEC/EN 60204-1 Emergency Stop requirements
- “Safe Break Action” ensures NC contacts will open if the contact block is damaged or separated from the actuator
- Models designed to interface with Safety BUS nodes/gateways

Illuminated Flush-mount E-Stop Push-Buttons

Description	Illumination***	Models
2NC / 1NO (PNP)	YEL/RED-Flash/Solid	SSA-EB1PLYR-12ED1Q8
2NC / 1NO (PNP)	YEL/RED-Flash/Solid, 1/2" NPT conduit connection with terminal strip	SSA-EB1PLYR-12ED1
2NC / 1NO (PNP)	GREEN/RED-Flash/Solid	SSA-EB1PLGR-12ED1Q8
2NC / 1NO (PNP)	GREEN/RED-Flash/Solid, 1/2" NPT conduit connection with terminal strip	SSA-EB1PLGR-12ED1
2NC / 1NO (PNP)	OFF/RED-Flash/Solid	SSA-EB1PLXR-12ED1Q8
2NC / 1NO (PNP)	OFF/RED-Flash/Solid, with 60 mm button	SSA-EB2PLXR-12ED1Q8
2NC / 1NO (PNP)	OFF/RED-Flash/Solid, 1/2" NPT conduit connection with terminal strip	SSA-EB1PLXR-12ED1
2NC / 1NO (PNP)	OFF/RED-Solid/Solid	SSA-EB1PL-12ED1Q8
2NC – Safety BUS node compatible*	YEL/RED-Flash	SSA-EB1PLYR-02ED1Q5A
2NC – Safety BUS node compatible*	OFF/RED-Flash	SSA-EB1PLXR-02ED1Q5A
2NC – Safety BUS node compatible*	OFF/RED-Solid	SSA-EB1PL-02ED1Q5A
2NC – Safety BUS node compatible**	YEL/RED-Flash	SSA-EB1PLYR-02ED1Q5B
2NC – Safety BUS node compatible**	OFF/RED-Flash	SSA-EB1PLXR-02ED1Q5B
2NC – Safety BUS node compatible**	OFF/RED-Solid	SSA-EB1PL-02ED1Q5B

For more specifications see page 609.

Connection options: A model with a QD requires a mating cordset (see page 606).

* CH1 = pins 1 & 2, CH2 = pins 4 & 5, 5-pin M12 QD

** CH1 = pins 1 & 4, CH2 = pins 2 & 5, 5-pin M12 QD

*** For EZ-LIGHT Illumination logic see page 607.