

E-Stop Buttons

30 mm Mount



- Allows for easy installation with no assembly or individual wiring required
- Rugged design
- Push-to-stop, twist-to-release or pull-to-release operation per IEC 60947-5-5
- Compliant with ANSI B11.19, ANSI NFPA79 and IEC/EN 60204-1 Emergency Stop requirements
- “Safe Break Action” ensures NC contacts will open if the contact block is damaged or separated from the actuator
- Models designed to interface with Safety BUS nodes/gateways

Base-mount E-Stop Push-Buttons

Description	Models
2NC	SSA-EB1P-02ECQ4
1NC / 1NO	SSA-EB1P-11ECQ4
2NC – Safety BUS node compatible*	SSA-EB1P-02ECQ5A
2NC – Safety BUS node compatible with 60 mm button*	SSA-EB2P-02ECQ5A
2NC – Safety BUS node compatible**	SSA-EB1P-02ECQ5B
2NC – Safety BUS node compatible with 60 mm button**	SSA-EB2P-02ECQ5B
2NC / 2NO	SSA-EB1P-22ECQ8
4NC with 60 mm button	SSA-EB2P-04ECQ8

For more specifications see page 609.

 Connection options: A model with a QD requires a mating cordset (see page 606).

* CH1 = pins 1 & 2, CH2 = pins 4 & 5, 5-pin M12 QD

** CH1 = pins 1 & 4, CH2 = pins 2 & 5, 5-pin M12 QD