


ACCESSORIES

BRACKETS

CORDSETS

RETROREFLECTORS

RMB100 (All measurements in mm)




- Hole center spacing:
 A, B, A to $B = 92$,
 C, D, C to $D = 77$, $B = 56$
 Hole size:
 $A, B, C, D = \varnothing 0.5$,
 $E = \varnothing 4.8$, $F = \varnothing 4.5$, $G = 21.5 \times 4.5$
- Protective mounting bracket for retroreflective targets
 - 14-ga. 316 stainless steel
 - Stainless steel M3 x 0.5 hardware included

Used with:
 BRT-3
 BRT-84

BRT-77X77C
 BRT-92X92C
 BRT-92X92CB

RMB50 (All measurements in mm)




- Hole center spacing:
 $A, B = 34$, A to $B = 52$, $E = 26$
 Hole size:
 $A, B = \varnothing 0.5$, $C = \varnothing 6.3$, $D = \varnothing 4.5$,
 $E = 13.8 \times 4.5$
- Protective mounting bracket for retroreflective targets
 - 14-ga. 316 stainless steel
 - Stainless steel M3 x 0.5 hardware included

Used with:
 BRT-50D
 BRT-50R
 BRT-2X2

BRT-51X51BM
 BRT-60X40AF
 BRT-60X40C
 BRT-60X40IP69K


RMB85 (All measurements in mm)



- Hole center spacing:
 A, B, A to $B = 77$, $E = 46$
 Hole size:
 $A, B = \varnothing 0.5$, $C = \varnothing 4.8$, $D = \varnothing 4.5$,
 $E = 19 \times 4.5$
- Protective mounting bracket for retroreflective targets
 - 14-ga. 316 stainless steel
 - Stainless steel M3 x 0.5 hardware included

Used with:
 BRT-3
 BRT-77X77C

SMB50RFA.. (All measurements in mm)




Model	Bolt Thread (A)
SMB50RFA	3/8 - 16 x 2"
SMB50RFAM10	M10 - 1.5 x 50

- Hole center spacing:
 $B = 5.4$
 Hole size:
 $B = 5.4$
 - Swivel bracket with tilt and pan movement for precision adjustment
 - Easy sensor mounting to extruded rail T-slots
 - 50 mm diameter plate for mounting a reflector

Used with:
 BRT-35DM
 BRT-50D

BRT-42D
 BRT-34T

SMBAMSR85P (All measurements in mm)




- Hole center spacing:
 $A = 26$, $B = 13$, $C = 77$, $E = 30$
 Hole size:
 $A = 26.8 \times 7$, $B = \varnothing 6.5$,
 $C = 2.3$, $D = 3.2$, $E = 3.2$
- Flat SMBAMS series bracket for mounting reflectors
 - Articulation slots for 90+° rotation
 - 14-ga. 300 series stainless steel

Used with:
 BRT-3
 BRT-84

BRT-77X77C
 BRT-51X51BM

MSMB-MSM-45 (All measurements in mm)




- Hole center spacing:
 A to $B = 50.8$
 Hole size:
 $A = \varnothing 7$, $B = 87.7 \times 7$
- Bracket for 45° mounting of mirror
 - 11-ga. cold-rolled steel with black corrosion-resistant zinc chromate finish
 - Bracket hardware included

Used with:
 MSM4A Mirror

NOTE:
 For a kit containing a bracket and MSM4A mirror, order model number MSA-MBM-K45


MSMMB (All measurements in mm)



- Hole center spacing:
 $A = 44.5$
 Hole size:
 $A = 10.2 \times 4.8$, $B = \varnothing 13.2$
- Replacement (pair) for brackets that come with MSM mirrors
 - 11-ga. cold-rolled steel with black corrosion-resistant zinc chromate finish
 - Bracket hardware included

Used with:
 MSM Mirror

LMBWLB92 (All measurements in mm)



- Hole center spacing: $B = 45$, $A = 124.6$
 Hole size: $A, B = 4 \times \varnothing 7.0$
- Stainless steel
 - Surface mount
 - Hardware included

Used with:
 WLB92