



DX80G2M6S-PM2

PM SERIES - WIRE REPLACEMENT



PM Series Gateway -LCD Selectable I/O Mapping
2.4 GHz, IP67 /NEMA 6
Inputs:Four selectable NPN/PNP discrete
Two 0-20mA
Outputs: Four PNP discrete; Two 0-20 mA
Part Number: 87097

CERTIFICATIONS



SPECIFICATIONS

Housing Style	Enclosed Terminals
Device Type	Gateway
Analog Inputs	Yes
Analog Outputs	Yes

Discrete Outputs	Yes
Input Details	4 Selectable Discrete, 2 0-20 mA Analog
Output Details	4 Sourcing Discrete, 2 0-20mA Analog
Power Supply	10-30V dc
Environmental Rating (IP)	IP67
Environmental Rating (NEMA)	NEMA 6
LCD Display	Yes
Max Operating Temperature (°C)	85
Min Operating Temperature (°C)	-40
Relative Humidity	95%
Point-to-Multipoint Topology	Yes
Point-to-Point Topology	Yes
Star Topology	Yes
Tree Topology	No
Feature: Hazardous Area	No
Modbus RTU	Yes
RS-485	Yes
Wireless	Yes
Radio Frequency	2.4 GHz
Input/Output	Analog & Discrete