



S18LGRYPQ

► BARREL-MOUNT INDICATORS: S18L SERIES



S18 EZ-LIGHT - 18 mm - IP67

Three Color: Green Red Yellow

10-30 V dc PNP Input

Euro 4-pin Quick-Disconnect

Part Number: 21290

CERTIFICATIONS



SPECIFICATIONS

Housing Style	Barrel
Primary Housing Material	Polycarbonate
Indication	Yes
Product Type	Indicator
Mounting Thread	18 mm
Color Input Control	Individual (One wire/color, same number of colors as input wires)
Color Option 1/Job Light	Green
Color Option 2	Red

Current - Color (mA)	25
Connection Type	Integral QD
Number of Pins/Conductors	4
Supply Voltage	10-30 V dc
Input Type	PNP
Max Input Response Time (ms)	1
Size/Length (mm)	18
Environmental Rating	IP67; IP69K
Max Op. Relative Humidity Non-Condensing (%)	95% @ 50°C
Max Op. Temperature (°C)	50
Min Op. Temperature (°C)	-40
Primary Window Material	Thermoplastic
Vibration and Mechanical Shock	Meets Mil. Std. 202F requirements method 201A. Also meets IEC 947-5-2; 30G 11 ms duration, half sine wave.
Feature: Washdown Rated	Yes
Feature: Hazardous Area	No
Feature: Audible	No
Feature: Chemical Resistant	No
Multi-Color Device	Single Color On
Indicator Light	Yes
IO Link	No
Modbus RTU	No