



SG-TL70-B

▶ TL70 MODULAR LED TOWER LIGHT SEGMENTS



TL70 Light Module; Color: Blue

Voltage: 12-30 V dc; Environmental Rating: IP65

Steady On/Flashing

Black Housing

Part Number: 92214

CERTIFICATIONS



SPECIFICATIONS

Housing Style	Segment - Light
Primary Housing Material	Polycarbonate
Indication	Yes
Color Option 1/Job Light	Blue
Current - Color (mA)	420
Supply Voltage	12-30 V dc
Input Type	Bimodal (PNP/NPN)
Max Input Response Time (ms)	50
Max Current - Audible Alarm (mA)	30

Environmental Rating	IP65
Max Op. Relative Humidity Non-Condensing (%)	95% @ 50°C
Max Op. Temperature (°C)	50
Min Op. Temperature (°C)	-40
Primary Housing Color	Black
Feature: Audible	No
Feature: Chemical Resistant	No
Multi-Color Device	Simultaneous Colors On

RELATED PRODUCTS

ACCESSORIES

	SSA-MBK-EEC1
	Bracket: E-STOP 30 mm Mounting Hub Bracket Right Angle; One Hole
	SMB30A
	Bracket: Right Angle Mounting; Material: 12 Gauge Stainless Steel; Curved mounting slot for versatility/orientation ; Clearance for M6 (1/4 in.) hardware
	SMB30MM
	Bracket: 30mm; Material: 12 Gauge Stainless Steel; Curved mounting slot for versatility/orientation ; Clearance for M6 (1/4 in.) hardware
	SMBAMS30P
	Bracket: 30 mm flat bracket; Material: 12 Gauge Cold Rolled Steel; Curved mounting slot for versatility/orientation
	SA-FFB12
	Bracket: Flush Foldable Bracket to 1/2 NPSM Black
	SA-FFB12C
	Bracket: Flush Foldable Bracket to 1/2 NPSM Gray