



SG-TL70-BC

▶ TL70 MODULAR LED TOWER LIGHT SEGMENTS



TL70 Light Module; Color: Blue

Voltage: 12-30 V dc; Environmental Rating: IP65

Steady On/Flashing

Gray Housing

Part Number: 92219

CERTIFICATIONS



SPECIFICATIONS

Housing Style	Segment - Light
Primary Housing Material	Polycarbonate
Indication	Yes
Product Type	Indicator
Color Option 1/Job Light	Blue
Current - Color (mA)	420
Supply Voltage	12-30 V dc
Input Type	Bimodal (PNP/NPN)
Max Input Response Time (ms)	50

Width/Diameter (mm)	70
Environmental Rating	IP65
Max Op. Relative Humidity Non-Condensing (%)	95% @ 50°C
Max Op. Temperature (°C)	50
Min Op. Temperature (°C)	-40
Primary Housing Color	Gray
Feature: Audible	No
Feature: Chemical Resistant	No
Multi-Color Device	Simultaneous Colors On
Indicator Light	Yes

RELATED PRODUCTS

ACCESSORIES

	SSA-MBK-EEC1 Bracket: E-STOP 30 mm Mounting Hub Bracket Right Angle; One Hole
	SMB30A Bracket: Right Angle Mounting; Material: 12 Gauge Stainless Steel; Curved mounting slot for versatility/orientation ; Clearance for M6 (1/4 in.) hardware
	SMB30MM Bracket: 30mm; Material: 12 Gauge Stainless Steel; Curved mounting slot for versatility/orientation ; Clearance for M6 (1/4 in.) hardware
	SMBAMS30P Bracket: 30 mm flat bracket; Material: 12 Gauge Cold Rolled Steel; Curved mounting slot for versatility/orientation
	SA-FFB12 Bracket: Flush Foldable Bracket to 1/2 NPSM Black