



# SSA-EB1P-02ECQ4

## ▶ 30 MM MOUNT EMERGENCY STOP BUTTONS



SSA-EB1 30 mm Mount Emergency Stop Push Button:  
Non-illuminated base; 40 mm Actuator  
IP65; Contacts: 2NC; M12 4-pin QD  
Part Number: 25298

### CERTIFICATIONS



### SPECIFICATIONS

|                               |               |
|-------------------------------|---------------|
| Housing Style                 | Base          |
| Device Type                   | Buttons       |
| Primary Housing Material      | Polycarbonate |
| Actuation                     | Push Button   |
| Feature: Non-Illuminated      | Yes           |
| Min Operating Temperature Ě°C | -25           |
| Dimensions (HxWxD mm )        | 120 x 80      |
| Max Operating Temperature Ě°C | 60            |
| IP Rating                     | IP65          |

|                          |               |
|--------------------------|---------------|
| Contact Rating           | 2 A @ 24 V dc |
| Contact Quantity         | 2 NC          |
| Mounting Hole Dia. (mm)  | 30            |
| Button Diameter (mm)     | 40            |
| Connection Type          | M12 (Euro)    |
| Actuator/Button Material | Thermoplastic |
| Mounting Thread/Style    | 30 mm         |

## RELATED PRODUCTS

### DOUBLE ENDED CORDSETS

|                                                                                                                                                                  |                    |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|
|                                                                                 | <b>DEE2R-5100D</b> |
| Euro-Style Quick Disconnect Cable Double-Ended; 5-pin Male Connector Straight; 5-pin Female Connector Straight, 30.50 m Length; Nickel Plated Brass Coupling Nut |                    |
|                                                                               | <b>DEE2R-515D</b>  |
| Euro-Style Quick Disconnect Cable Double-Ended; 5-pin Male Connector Straight; 5-pin Female Connector Straight, 4.57 m Length; Nickel Plated Brass Coupling Nut  |                    |
|                                                                               | <b>DEE2R-51D</b>   |
| Euro-Style Quick Disconnect Cable Double-Ended; 5-pin Male Connector Straight; 5-pin Female Connector Straight, 0.30 m Length; Nickel Plated Brass Coupling Nut  |                    |
|                                                                               | <b>DEE2R-525D</b>  |
| Euro-Style Quick Disconnect Cable Double-Ended; 5-pin Male Connector Straight; 5-pin Female Connector Straight 7.62 m Length; Nickel Plated Brass Coupling Nut   |                    |
|                                                                               | <b>DEE2R-53D</b>   |
| Euro-Style Quick Disconnect Cable Double-Ended; 5-pin Male Connector Straight; 5-pin Female Connector Straight, 0.91 m Length; Nickel Plated Brass Coupling Nut  |                    |
|                                                                               | <b>DEE2R-550D</b>  |
| Euro-Style Quick Disconnect Cable Double-Ended; 5-pin Male Connector Straight; 5-pin Female Connector Straight, 15.20 m Length; Nickel Plated Brass Coupling Nut |                    |