



SSA-EB1PLYR-12ED1Q8

▶ FLUSH-MOUNT EMERGENCY STOP BUTTON



Emergency Stop: Flush Mounting 40mm Push Button

Environ. Rating: IP65; Lighted; Color: Yellow, Red Solid/Flashing

2 N.C. safety contacts; 1 N.O. aux. contacts

8 Pin Euro-style Quick-Disconnect Connector,

Part Number: 29989

CERTIFICATIONS



SPECIFICATIONS

Housing Style	Flat
Device Type	Buttons
Primary Housing Material	Polycarbonate
Actuation	Push Button
Min Operating Temperature ÷?C	-25

Max Operating Temperature ÷°C	55
IP Rating	IP65
Stop Signal Color (Solid)	Red
Emergency Stop	Yes
Actuated Color	Red - Flash
Contact Rating	2 A @ 24 V dc
Contact Quantity	2 NC, 1 NO
Button Diameter (mm)	40
Armed Color (Solid)	Yellow
Connection Type	M12 (Euro)
Actuator/Button Material	Thermoplastic
Mounting Thread/Style	Flat

RELATED PRODUCTS

DOUBLE ENDED CORDSETS

	DEE2R-8100D
Euro-style Quick Disconnect Cable; Double-ended; 8 Pin Male Connector Straight; 8 Pin Female Connector Straight; 30.48 m Length; Chrome plated brass coupling nut	
	DEE2R-815D
Euro-style Quick Disconnect Cable; Double-ended; 8 Pin Male Connector Straight; 8 Pin Female Connector Straight; 4.57 m Length; Chrome plated brass coupling nut	
	DEE2R-81D
Euro-style Quick-Disconnect Cable ; 8 Pin Double Ended With 1 Female & 1 Male Connector; 0.3 m (1 ft) in Length; 22 GA Cascadeable	
	DEE2R-825D
Euro-style Quick Disconnect Cable; Double-ended; 8 Pin Male Connector Straight; 8 Pin Female Connector Straight; 7.62 m Length; Chrome plated brass coupling nut	