



DX80K2M6-PM2

► **PM SERIES - WIRE REPLACEMENT**



PM2 Series Kit
Includes one gateway and one node
pre-mapped and pre-bound
2.4 GHz 100 mW
LCD Selectable I/O Mapping
IP67 / NEMA 6
In: Four selectable NPN/PNP discrete; Two 0-20 mA
Part Number: 92938

SPECIFICATIONS

Housing Style	Enclosed Terminals
Device Type	Kit
Input/Output	Analog & Discrete
Analog Inputs	Yes
Analog Outputs	Yes
Discrete Inputs	Yes
Discrete Outputs	Yes
Input Details	4 Selectable Discrete, 2 0-20 mA Analog
Output Details	4 Sourcing Discrete, 2 0-20mA Analog

Power Supply	10-30V dc
Environmental Rating (IP)	IP67
Environmental Rating (NEMA)	NEMA 6
LCD Display	Yes
Max Operating Temperature (°C)	85
Min Operating Temperature (°C)	-40
Relative Humidity	95%
Point-to-Multipoint Topology	Yes
Point-to-Point Topology	Yes
Star Topology	Yes
Tree Topology	No
Feature: Hazardous Area	No
EtherNet/IP	No
Modbus RTU	Yes
Modbus/TCP	No
RS-232	No
RS-485	Yes
Wireless	Yes
Wireless Radio Frequency	2.4 GHz
1-wire Serial Interface	No



