



DX80K2M6-PM8

► PM SERIES - WIRE REPLACEMENT



PM8 Series Kit
Includes one gateway and one node
pre-mapped and pre-bound
2.4 GHz 100 mW
LCD Selectable I/O Mapping
IP67 / NEMA 6
Inputs: Six selectable NPN/PNP discrete
Outputs: Six PNP discrete
Part Number: 92940

CERTIFICATIONS



SPECIFICATIONS

Housing Style	Enclosed Terminals
Device Type	Kit
Input/Output	Discrete
Discrete Inputs	Yes
Discrete Outputs	Yes
Input Details	6 PNP Discrete
Output Details	6 PNP Discrete

Power Supply	10-30V dc
Environmental Rating (IP)	IP67
Environmental Rating (NEMA)	NEMA 6
LCD Display	Yes
Max Operating Temperature (°C)	85
Min Operating Temperature (°C)	-40
Relative Humidity	95%
Point-to-Multipoint Topology	Yes
Point-to-Point Topology	Yes
Star Topology	Yes
Tree Topology	No
Feature: Hazardous Area	No
EtherNet/IP	No
Modbus RTU	Yes
Modbus/TCP	No
RS-232	No
RS-485	Yes
Wireless	Yes
Wireless Radio Frequency	2.4 GHz
1-wire Serial Interface	No



