



DX80K9M6-PM8

► **PM SERIES - WIRE REPLACEMENT**



PM8 Series Kit
Includes one gateway and one node
pre-mapped and pre-bound
900 MHz 1Watt / 250 mW
LCD Selectable I/O Mapping
IP67 / NEMA 6
Inputs: Six selectable NPN/PNP discrete
Outputs: Six PNP discrete
Part Number: 92939

SPECIFICATIONS

Housing Style	Enclosed Terminals
Device Type	Kit
Input/Output	Discrete
Discrete Inputs	Yes
Discrete Outputs	Yes
Input Details	6 PNP Discrete
Output Details	6 PNP Discrete
Power Supply	10-30V dc
Environmental Rating (IP)	IP67

Environmental Rating (NEMA)	NEMA 6
LCD Display	Yes
Max Operating Temperature (°C)	85
Min Operating Temperature (°C)	-40
Relative Humidity	95%
Point-to-Multipoint Topology	Yes
Point-to-Point Topology	Yes
Star Topology	Yes
Tree Topology	No
Feature: Hazardous Area	No
EtherNet/IP	No
Modbus RTU	Yes
Modbus/TCP	No
RS-232	No
RS-485	Yes
Wireless	Yes
Wireless Radio Frequency	900 MHz
1-wire Serial Interface	No



Banner Engineering Corp. | 9714 Tenth Avenue North | Minneapolis, MN 55441 | United States of America

