



DX80N2Q120BL-RG

▶ PRODUCTS FOR INDUSTRIAL AUTOMATION



Wireless Q120 Node 2.4 GHz 65 mW
Battery Included and 10 - 30 V dc power terminals
Six independently controlled push button inputs
Six sets of green and red LED indicator lights
Part Number: 800826

SPECIFICATIONS

Housing Style	Integrated Battery
Device Type	Push Button
Input/Output	Discrete
Discrete Inputs	Yes
Discrete Outputs	Yes
Input Details	Six Buttons
Output Details	Twelve LED lights
Power Supply	D-Cell Lithium
Relative Humidity	90% at 50° C
Point-to-Multipoint Topology	Yes
Point-to-Point Topology	Yes
Star Topology	Yes

Tree Topology	No
Feature: Hazardous Area	No
Indicator Light	Yes
EtherNet/IP	No
Modbus RTU	No
Modbus/TCP	No
RS-232	No
RS-485	No
Wireless	Yes
Wireless Radio Frequency	2.4 GHz
1-wire Serial Interface	No
Ships With Battery	Yes

RECOMMENDED PRODUCTS

BATTERY PACKS

	BWA-BATT-011 Replacement Battery; 3.6V D Lithium Cell Standard
---	---



Banner Engineering Corp. | 9714 Tenth Avenue North | Minneapolis, MN 55441 | United States of America

