

POWERED TO REACH

everywhere you need
to clean.

NuTone current-carrying hoses bring the power to wherever your vacuum reaches. We offer a wide selection of lightweight, flexible hoses including direct-connect options for use with electrified inlets. Current-carrying hoses allow you to operate an electric power brush without using an additional cord set.

And, the comfortable handle design and fingertip controls on the handle grip add comfort and convenience to your cleaning. The large hose diameter provides better dirt removal. All NuTone hoses come with a convenient storage hanger.



CURRENT-CARRYING HOSES



CH615

Direct Connect Lightweight, Crushproof Hose

This lightweight, current-carrying direct-connect hose springs back to retain original shape. Features a 3-position on-off switch. **Available in dark gray.**

- Recommended for use with NuTone CI358 and CI390 series electrified inlets
- For use with NuTone CT700 Deluxe Electric Power Brush
- UL approved
- 30' length
- Includes convenient hose hanger to store hose



CH515

Dual-Voltage Lightweight, Crushproof Hose with Pigtail

This lightweight, current-carrying corded hose springs back to retain original shape. Features a 3-position on-off switch and 6' line cord. **Available in dark gray.**

- For use with NuTone CT700 Deluxe Electric Power Brush
- Includes Universal hose end which fits all NuTone and most other standard inlets
- UL approved
- 30' length
- Includes convenient hose hanger to store hose

HOSE ACCESSORIES



CA130

A knitted hose sock can help prevent scratching corners of walls and marking furniture as you move from room to room while vacuuming.

- Washable
- Treated with ultra fresh antimicrobial protection
- For 30-32' hoses



1. Fit sock over tube end
2. Slide entire sock onto tube
3. Feed nozzle end through tube
4. Slide sock off tube onto hose; zip tie at handle
5. Slide sock off of tube to cover remainder of the hose

HOSE SELECTION CHART

Model No.	Description	Hose Length	Inside Diameter	Power Head Switch	Power Unit Switch	Color
372	Low Voltage Utility/Garage Hose	32'	1-1/4"	No	No	Dark Gray
CH230L	Low Voltage Standard Hose	42'	1-3/8"	No	Yes	Dark Gray
CH235	Crushproof Low Voltage Hose	30'	1-3/8"	No	Yes	Dark Gray
CH515	Current-Carrying Crushproof Hose w/Status Indicator Light	30'	1-1/4"	Yes	Yes	Dark Gray
CH615	Direct-Connect Crushproof Hose w/Status Indicator Light	30'	1-1/4"	Yes	Yes	Dark Gray

HOSE ACCESSORIES

Model No.	Description	Hose Length	Inside Diameter	Color
CA130	Hose Sock	30' -32'	1" & 1-3/8" diameter hoses	Gray

PLUG INTO POWER AND CONVENIENCE

with NuTone Inlets.

Turn to the source for power and intelligence. NuTone’s line of central cleaning inlets include built-in, low-voltage terminals where direct-connect hoses plug right into the inlet – alleviating the need for a power cord. The electrified inlets make it a simple one-step operation to plug in a current-carrying hose.

The system turns on automatically when an unswitched hose is inserted or is ready for immediate activation with a switched hose.

NuTone inlets are the source of ease and convenience when working with a central vacuum system.

ELECTRIFIED INLETS

Electrified Inlets make it a simple one-step operation to plug in a Current-Carrying hose – no 120V extension cord to carry around. Compatible with NuTone CH615.



White

CI390 Series

Standard

The ElectraValve® Electrified Inlet operates on standard house wiring. It eliminates the need for the extension of electrical cords from the inlet to an electrical outlet. The molded power receptacle clips to a mounting plate and the housing wire is run to the nearest outlet box.

- UL listed Assembly
- Available in white or almond



White

CI358W

Supervalue

The Supervalve Electrified Inlet operates on standard house wiring. Includes wall valve, rough-in plate with junction box and strain relief.

- UL listed assembly

CI395RK

Rough-In Kit

The Electrified Inlet Rough-In Kit includes everything you need to install the CI390. Includes mounting plate, snap-in power receptacle, 6' of 12-gauge cable assembly, plaster guard, CF382S elbow and mounting screws for plaster guard.



HOSE-INLET COMPATIBILITY

		INLET TYPE					
HOSE TYPE		CI390W	CI358W	360W	330W	CF372	
	Current Carrying	CH615	●	●			●
		*CH515	○	○	●	●	●
	Low Voltage	372			○	○	●
		CH235	○	○	●	●	○
		CH230L	○	○	●	●	

* Includes 6' line cord ● Full Function ○ Limited Function (suction only/non-powered)