




K50LNGXXPQ

K50 CORE SERIES 50 MM GENERAL PURPOSE LED INDICATOR



K50LN Series EZ-LIGHT: 1-Color Hazardous Area Indicator

Protection Type: Ex nA_Ex tc

Voltage: 10-30 V dc; Housing: Polycarbonate; IP67

Input: PNP; Colors: Green

Euro-style Quick-Disconnect

Part Number: 26934

CERTIFICATIONS



SPECIFICATIONS

Housing Style	Base Mount - Dome Window
Primary Housing Material	Polycarbonate
Indication	Yes
Mounting Thread	M30 x 1.5
Color Input Control	Individual (One wire/color, same number of colors as input wires)
Number of Colors / Segments	1

Product Size (mm)	50
Color Technology	Standard LED
Color Option 1	Green
Animation Option 1	Solid On
Max Current Color (mA)	25
Connection Type	Integral QD
QD Type/Cable Length	M12 (Euro) requires mating cordset
Number of Input Pins/Conductors	4
Supply Voltage	10-30 V dc
Input Type	PNP
Physical Dimensions (LxWxH or DxH mm)	50.0 x 69.0
Environmental Rating	IP67; IP69K
Max Op. Temperature (°C)	50
Min Op. Temperature (°C)	-40
Primary Housing Color	Black
Primary Window Material	Polycarbonate Diffused
Feature: Washdown Rated	Yes
Feature: Hazardous Area	Yes
Feature: Audible	No
Feature: Chemical Resistant	No
Multi-Color Device	Single Color On
IO Link	No
Modbus RTU	No
Wireless	No
Pro-Editor Compatible	No

COMPATIBLE PRODUCTS

BRACKET

	SMB30A Bracket: Right Angle Mounting; Material: 12 Gauge Stainless Steel; Curved mounting slot for versatility/orientation ; Clearance for M6 (1/4 in.) hardware
	SMB30SC Bracket: Compact 30 mm Swivel; Black reinforced thermoplastic polyester; Wide Range of Articulation ; Hardware included
	SMB30FA SMB30FA Bracket: Swivel with Tilt and Pan Movement 30mm Mounting Hole 3/8-16x2in Bolt Thread Mount
	SMB30FVK SMB30FVK Bracket: V-Clamp Flat with Fasteners for Mounting Sensor with 30mm Threads to Pipe or Extrusions 32.6mm (1.28in)
	SMB30MM Bracket: 30mm; Material: 12 Gauge Stainless Steel; Curved mounting slot for versatility/orientation ; Clearance for M6 (1/4 in.) hardware
	SMB30Q Bracket: 30 mm Angle Flanged Mounting; For use with Q40 Sensors
	SMB30RAVK Bracket: V-Clamp Mount; 30 mm hole to 28 mm tube; Right-angle
	SMBAMS30P Bracket: 30 mm flat bracket; Material: 12 Gauge Cold Rolled Steel; Curved mounting slot for versatility/orientation
	SMBAMS30RA Bracket: 30mm Right Angle; Material: 12 Gauge cold rolled steel; Curved mounting slot for versatility/orientation
	SMBAMS30PL52R Bracket: Flat SMBAMS series with space; for 60 x 58 mm label; 30 mm hole for mounting sensors; Articulation slots for 90 plus degree rotation; 12-ga. (2.6 mm) Cold-rolled Steel

	SMBAMS30RLJ Bracket: Right-angle SMBAMS series with 70 x 40 mm space for label; 30 mm hole for mounting sensor; Articulation slots for 90 plus degree rotation; 12-ga. (2.6 mm) Cold-rolled Steel
	SMBAMS30RLS Bracket: Right Angle; 30 mm hole; Small Legend, Automotive Industry;
	SA-M30E12 SA-M30E12 Streamlined Black Acetal Stand-Off Pipe Adaptor/Cover with M30x1.5 Threads for use with K50 EZ-LIGHT
	SOP-E12-150A Accessory: 150 mm elevated-use stand-off pipe (1/2 in. NPSM/DN15); Material: Anodized Aluminum(BLACK); 1/2 NPT thread at both ends; Compatible with most industrial environments
	SOP-E12-300A Accessory: 300 mm elevated-use stand-off pipe (1/2 in. NPSM/DN15); Material: Anodized Aluminum(BLACK); 1/2 NPT thread at both ends; Compatible with most industrial environments
	SOP-E12-900A Accessory: 900 mm elevated-use stand-off pipe (1/2 in. NPSM/DN15); Material: Anodized Aluminum(BLACK); 1/2 NPT thread at both ends; Compatible with most industrial environments
	SOP-E12-150AC Accessory: 150 mm elevated-use stand-off pipe (1/2 in. NPSM/DN15); Material: Anodized Aluminum(CLEAR); 1/2 NPT thread at both ends; Compatible with most industrial environments
	SOP-E12-300AC Accessory: 300 mm elevated-use stand-off pipe (1/2 in. NPSM/DN15); Material: Anodized Aluminum(CLEAR); 1/2 NPT thread at both ends; Compatible with most industrial environments
	SOP-E12-900AC Accessory: 900 mm elevated-use stand-off pipe (1/2 in. NPSM/DN15); Material: Anodized Aluminum(CLEAR); 1/2 NPT thread at both ends; Compatible with most industrial environments
	SOP-E12-150SS Accessory: 150 mm elevated-use stand-off pipe (1/2 in. NPSM/DN15); Material: Stainless steel; 1/2 NPT thread at both ends; Compatible with most industrial environments
	SOP-E12-300SS Accessory: 300 mm elevated-use stand-off pipe (1/2 in. NPSM/DN15); Material: Stainless steel; 1/2 NPT thread at both ends; Compatible with most industrial environments

	SOP-E12-900SS Accessory: 900 mm Elevated-use Stand-off Pipe (1/2 in. NPSM/DN15); Material: Stainless steel; 1/2 NPT Thread at both ends; Compatible with most industrial environments
	SA-E12M30 Accessory: Mounting base adapter/cover; Material: Acetal; 1/2 in. NPSM/DN15 pipe and 30 mm (1-3/16 in.) drilled hole; Mounting hardware included
	SA-E12M30C Accessory: Mounting base adapter/cover; Material: White UHMW; 1/2 in. NPSM/DN15 pipe and 30 mm (1-3/16 in.) drilled hole; Mounting hardware included
	SA-FFB12 SA-FFB12 Bracket: Flush Foldable Bracket for use with Elevated Mount Systems
	SA-FFB12C Bracket: Flush Foldable Bracket to 1/2 NPSM Gray
	LMB30RA Bracket: Indicator Light Mounting; Right Angle; Fits M30 X 1.5 Base; Color: Black
	LMB30RAC Bracket: Indicator Light Mounting; Right Angle; Fits M30 X 1.5 Base; Color: Gray
	LMBE12RA Bracket: Indicator Light Mounting; Right Angle; Fits 1/2 in NPSM Pipe; Color: Black
	LMBE12RAC Bracket: Indicator Light Mounting; Right Angle; Fits 1/2 in NPSM Pipe; Color: Gray

SINGLE-ENDED CORDSETS

	MQDC-406 Euro-style Quick Disconnect Cable; 4-Pin Straight Connector; 2 m (6.5 ft) in Length; Nickel-plated Brass Coupling Nut
	MQDC-415 Euro-style Quick Disconnect Cable; 4-Pin Straight Connector; 5 m (15 ft) in Length; Nickel-plated Brass Coupling Nut.

	MQDC-430 Euro-Style Quick Disconnect Cable; 4-Pin Straight Connector; 9 m (30 ft) in Length; Nickel-plated Brass Coupling Nut
	MQDC-450 Euro-Style Quick Disconnect Cable; 4-Pin Straight Connector; 15 m (50 ft) in Length; Nickel-plated Brass Coupling Nut
	MQDC-406RA Euro-Style Quick Disconnect Cable; 4-Pin Right-Angle Connector; 2 m (6.5 ft) in Length; Nickel-plated brass coupling nut
	MQDC-415RA Euro-Style Quick Disconnect Cable; 4-Pin Right-Angle Connector; 5 m (15 ft) in Length; Nickel-plated brass coupling nut
	MQDC-430RA Euro-Style Quick Disconnect Cable; 4-Pin Right-Angle Connector; 9 m (30 ft) in Length; Nickel-plated brass coupling nut
	MQDC-450RA Euro-Style Quick Disconnect Cable; 4-Pin Right-Angle Connector; 15 m (50 ft) in Length; Nickel-plated brass coupling nut

MISCELLANEOUS

	K50DS K50DS K50 Daylight Shield
---	---



Banner Engineering Corp. | 9714 Tenth Avenue North | Minneapolis, MN 55441 | United States of America

