

Eaton 100D125

Catalog Number: 100D125

Eaton Bussmann series low voltage D fuse, 500V, 100A, 50 kAIC, Non Indicating, fuse, Class C gL/gG, Time delay, Holder, Red, Ceramic body



General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage D fuse	100D125
	UPC
	051712830249
EAN	Product Length/Depth
5027590427593	60 mm
Product Height	Product Width
33 mm	33 mm
Product Weight	Compliances
384.3333333 g	CE Marked
	GoST-R
	RoHS Compliant

Certifications

VDE
IEC 60269
DIN EN 60269-3 (VDE 0636 Part 30)
DIN EN 60269-1 (VDE 0636 Part 10)
DIN VDE 0636-301

defaultTaxonomyAttributeLabel

Type

fuse

Application

For domestic and general industrial applications

Amperage Rating

100 A

Fuse size

DIV

Breaking capacity

50 kA

Construction size (fuse inserts)

DIV

Rated voltage AC

500 V

Class

Class C gL/gG

Fuse type

D125 - Time delay

Accessory/spare part type

100GD125 Red screw cap gauge piece

Utilization category

gL/gG (cable protection/equipment protection)

Color

Red

Interrupt rating

50 kAIC

Fuse indicator

Non-indicating

Connection

Other

Construction

D4

Construction size

DIV

Fuse shape

Resources

Brochures

[eaton-bussmann-series-d-and-d0-fuses-product-aid-pa132014en-en-us.pdf](#)

Catalogs

CA134002EN

[100D125~Eaton Bussmann series low voltage D fuse](#)

[Bussmann series complete full line catalog no. 1007](#)

Compliance information

[UKCA Bottle fuse-links, holders, carriers and accessories](#)

[CE Bottle fuse-links, holders, carriers and accessories](#)

Technical data sheets

[4124 D and D0 fuses, bases and accessories](#)

Bottle

Response time

Time-delay

Suitable for

R1 1/4" / DIV Fuse base

Material

White ceramic body

Mounting method

Holder

Release characteristic

Time-lag

Quantity

10

Voltage rating

500 V



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.
All other trademarks are property of their respective owners.



Eaton.com/socialmedia